Data Sheet





Product Characteristics		
Model	cCore 6	
Storage Capacity	6TB (RAIDZ1)	
Available Storage	4TB	

The superior security benefits of a robust, high-quality on-premise information archiving solution apply not only to larger enterprises, but especially to businesses competing in the challenging SMB environment.

Maintain your competitive edge and ensure peace of mind with Jatheon's cCore 6, the first enterprise-grade all-in-one information archiving appliance. Automate compliance, ensure eDiscovery readiness and take control of your enterprise data to a new level with Jatheon's award-winning, industry-leading tools designed to help your business thrive.

Features	Availability
Remote System Monitoring	✓
Full Indexing & Archiving	✓
Message Compression	✓
Single Instance Storage	✓
Search & Retrieval	✓
Retention Policy Management	✓
Legal Hold	✓
Role-Based Administration	✓
Outlook Plugin	✓
Tamper-Proof OS & Storage	✓
Comprehensive Audit Trail	✓
Web-Based Interface	✓
Comprehensive Reporting and Statistics	✓







System

- Processor: Intel Xeon E3-1220 v6 3.0-3.5GHz (8MB L3 cache 4 cores / 4 threads)
- Memory: 32 GB ECC DDR4-2400
- Chipset: Intel C232
- Network Controllers: 2 x 1000BASE Gbit Ethernet
- IPMI Interface with dedicated LAN port

Chassis

- Form Factor: 1U rackmount
- Dimensions: 437mm(W) x 43mm(H) x 503mm(D)
- Cooling System: 4x 4cm 12.5K RPM, PWM fans

Storage

- Emergency SSD: 1 x 512GB SATA III 2.5"
- Hard Drives: 3 x 2TB SAS-3 12.0Gbps
 3.5" 128MB cache 7200RPM
- RAID-Z1 allows one disk to fail and preserve data integrity

Storage Expansion

Not available

ZFS

- Horizontal scalable expansion
- Self-healing
- Auto Bit Rot Recovery
- Unlimited file system snapshots for archive protection and backups
- Super-efficient file system replication
- Protection Against Data Corruption

Power Supply

- 350W high-efficiency (92%) AC-DC
- Input: 100-240 V, 50-60 Hz
- Output: 29 Amp @ +12V standby, 18
 Amp @ +5V, 15 Amp @ +3.3V

Front Panel

- Power On/Off button
- System Reset button
- Power status LED
- Hard drive activity LED
- 2x Network activity LEDs
- System Overheat LED
- Fan fail LED

Graphics

Aspeed AST2400 BMC

I/O Interfaces

- 6x SATA 3.0 ports (6Gbps)
- 8x SAS3 ports (12Gbps)
- 2x RJ45 Gigabit Ethernet LAN ports
 5x USB 3.0 ports (2 rear + 4 via header
 + 1 Type A)
- 6x USB 2.0 ports (2 rear + 4 via header)
- 1x VGA port
- 2 COM ports

Operating Environment / Compliance

- RoHS Compliant
- Operating Temperature: 0°C to 50°C (32°F to 122°F)
- Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)
- Operating Relative Humidity: 8% to 90% (non-condensing)
- Non-operating Relative Humidity: 5% to 95% (non-condensing)

Shipping Weight

- 41 lb