



AcryShield Safety Walkway System Installation Guide Specification

Saving Money, Safeguarding the Environment...One Roof at a Time.®

APPLICATION

National Coatings recommends the following procedure for any areas designated as walkways or high traffic areas such as access points and HVAC equipment on the Acryshield/Acryply systems:

Walkway Or High Traffic Areas

- *Walkways should be a minimum of 30" wide.*
- *Mask off area to receive walkway system to ensure clean straight edges.*
- *Apply 2 additional coats of AcryShield A510 or A550 at 1.5 gallons per 100 square feet*
- *Immediately after the application of the Acryshield Coating, broadcast white granules into the coating at a rate of 35 lbs. per 100 square feet. The granules will settle into the coating. Apply the granules generously, inspect the surface within a few minutes and reapply as needed to obtain a continuous film of granules.*
- *After the coating has completely cured, remove all loose granules with a small hand blower and a soft bristle broom*

Color of Acryshield applied in walkways to be determined by owner.

MATERIALS

The following materials listed in these recommendations are available from National Coatings Corporation:

1. AcryShield A510 or A550
2. Roofguard White Granules

The suggestions and data in this specification are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control. The prospective user should determine the suitability of our materials and installation recommendations before adopting them for commercial use.



NATIONAL COATINGS CORPORATION
1201 Calle Suerte, Camarillo, California 93012
(800) 423-9557 FAX (800) 294-3866
www.nationalcoatings.com

© 2017 National Coatings Corporation. All Rights Reserved.