



# FOUR SEASONS PREMIUM ACRYLIC COATING



**Four Seasons Premium** is a premium, multi-purpose, acrylic, elastomeric coating for use over a variety of substrates including asphalt, BUR, cap sheet, previous coatings, TPO, EPDM, SPF, concrete and metal roofing. Four Seasons 365 Acrylic Elastomeric Roof Coating provides durability, energy savings, prolonged roof life, reduced life cycle costs and a 12 year limited material warranty.

- Water-Based 100% Acrylic
- Reduced Life Cycle Costs
- Environmentally Friendly
- Seamless Waterproofing
- Asphalt Bleed Blocking
- Prolonged Roof Life
- Energy Savings
- Cost Effective
- Renewable

Property	Typical Results
Solids Content By Weight	66.9% ± 2
Solids Content By Volume	51.9% ± 2
Solar Reflectance aged	.76
Thermal Emittance aged	.90
SRI Aged	94
Tensile Strength	350 psi
Elongation	200%
Permeance, US Perms	19
Viscosity	110±10

## APPROVALS



## INSTALLATION

Clean all roof surfaces with Four Seasons 365 Roof Cleaner. All surfaces must be dry and free of dust, dirt, oil, loose coating, mildew, algae and all other foreign matter. Use Four Seasons 365 Peel and Stick Tape to bridge problematic seams and laps. Fill all cracks, holes, voids, splits and penetrations with Four Seasons 365 Acrylic Roof Patch & Sealant. Allow sealant to dry 12-24 hours. Using a 3/4" nap roller, prime entire roof with Four Seasons 365 Roof Primer at a spread rate of 100 sq. ft. per gallon. Allow primer to dry for 4-12 hours. Using a 3/4" nap roller, apply first topcoat of Four Seasons 365 Elastomeric Roof Coating at a spread rate of 50 sq. ft. per gallon. Allow topcoat to dry for 6-24 hours. Apply second topcoat of Four Seasons 365 Elastomeric Roof Coating at a spread rate of 50 sq. ft. per gallon. Allow topcoat to dry for 2-6 hours.

**STORAGE** - Store materials between 40°F and 100°F to prevent damage to products. Do not store at high temperatures or direct sunlight. Protect all materials from freezing during transit, handling, storage, and installation. Minimum one year shelf life if stored at 40°F-90°F.

**MAINTENANCE** - Periodic maintenance ensures extended performance and reduces life cycle costs.

**TECHNICAL SERVICES** - Additional information, product brochures, and guide specifications are available. Roof energy evaluations, life cycle cost analyses, and other roof management services are also available from a National Coatings Technical Consultant.

**WARRANTY** - National Coatings Corporation warrants for a period of twelve (12) years from the date of purchase that the coating applied is free of any defects in manufacturing. This guarantee is limited to replacement of the product at the expense of National Coatings, when such product proves to be defective in manufacture. Among other things, this warranty does not apply to failure due to improper application.

## Available Sizes

Product	Product Code	Unit Size	Unit Weight	Pack
Four Seasons 12 Year Premium Acrylic Coating - White 1 Gallon	FS12W-1	1 gal.	12 lbs	4
Four Seasons 12 Year Premium Acrylic Coating - White 5 Gallon	FS12W-5	5gal.	59 lbs	1
Four Seasons 12 Year Premium Acrylic Coating - Lt. Grey 1 Gallon	FS12G-1	1 gal.	12 lbs	4
Four Seasons 12 Year Premium Acrylic Coating - Lt. Grey 5 Gallon	FS12G-5	5 gal.	59 lbs	1



NATIONAL COATINGS CORPORATION  
1201 Calle Suerte Camarillo, CA 93012  
800-423-9557 [www.nationalcoatings.com](http://www.nationalcoatings.com)