



FOUR SEASONS ULTRA PREMIUM ACRYLIC COATING



Four Seasons Ultra Premium is a premium, multi-purpose, acrylic, elastomeric coating for use over a variety of substrates including asphalt, BUR, cap sheet, previous coatings, TPO, EPDM, SPF, concrete and metal roofing. Rain resistant in 30 minutes. Four Seasons 365 Acrylic Elastomeric Roof Coating provides durability, energy savings, prolonged roof life, reduced life cycle costs and a 20 year limited material warranty.

- Water-Based 100% Acrylic
- Reduced Life Cycle Costs
- Environmentally Friendly
- Rain Resistant in 30 Minutes
- Seamless Waterproofing
- Asphalt Bleed Blocking
- Prolonged Roof Life
- Energy Savings
- Cost Effective
- Renewable

Property	Typical Results
Solids Content By Weight	66% ± 2
Solids Content By Volume	52% ± 2
Solar Reflectance aged	.73
Thermal Emittance aged	.93
SRI Aged	91
Tensile Strength	385 psi
Elongation	140%
Permeance, US Perms	11
Viscosity	110±10

APPROVALS



INSTALLATION

Clean all roof surfaces with Four Seasons 365 Roof Cleaner. All surfaces must be dry and free of dust, dirt, oil, loose coating, mildew, algae and all other foreign matter. Use Four Seasons 365 Peel and Stick Tape to bridge problematic seams and laps. Fill all cracks, holes, voids, splits and penetrations with Four Seasons 365 Acrylic Roof Patch & Sealant. Allow sealant to dry 12-24 hours. Using a 3/4" nap roller, prime entire roof with Four Seasons 365 Roof Primer at a spread rate of 100 sq. ft. per gallon. Allow primer to dry for 4-12 hours. Using a 3/4" nap roller, apply first topcoat of Four Seasons 365 Elastomeric Roof Coating at a spread rate of 50 sq. ft. per gallon. Allow topcoat to dry for 6-24 hours. Apply second topcoat of Four Seasons 365 Elastomeric Roof Coating at a spread rate of 50 sq. ft. per gallon. Allow topcoat to dry for 2-6 hours.

STORAGE - Store materials between 40°F and 100°F to prevent damage to products. Do not store at high temperatures or direct sunlight. Protect all materials from freezing during transit, handling, storage, and installation. Minimum one year shelf life if stored at 40°F-90°F.

MAINTENANCE - Periodic maintenance ensures extended performance and reduces life cycle costs.

TECHNICAL SERVICES - Additional information, product brochures, and guide specifications are available. Roof energy evaluations, life cycle cost analyses, and other roof management services are also available from a National Coatings Technical Consultant.

WARRANTY - National Coatings Corporation warrants for a period of twenty (20) years from the date of purchase that the coating applied is free of any defects in manufacturing. This guarantee is limited to replacement of the product at the expense of National Coatings, when such product proves to be defective in manufacture. Among other things, this warranty does not apply to failure due to improper application.

Available Sizes

Product	Product Code	Unit Size	Unit Weight	Pack
Four Seasons 20 Year Ultra Premium Acrylic Coating - White 1 Gallon	FS20W-1	1 gal.	13 lbs	4
Four Seasons 20 Year Ultra Premium Acrylic Coating - White 5 Gallon	FS20W-5	5gal.	62 lbs	1
Four Seasons 20 Year Ultra Premium Acrylic Coating - Lt. Grey 1 Gallon	FS20G-1	1 gal.	13 lbs	4
Four Seasons 20 Year Ultra Premium Acrylic Coating - Lt. Grey 5 Gallon	FS20G-5	5 gal.	62 lbs	1



NATIONAL COATINGS CORPORATION
1201 Calle Suerte Camarillo, CA 93012
800-423-9557 www.nationalcoatings.com