



FOUR SEASONS POLYESTER REINFORCING FABRIC

Four Seasons Polyester Reinforcing Fabric is a 4-inch wide, high tensile strength, 100% polyester stitch-bonded fabric tape for sealing edges, seams, flashings, fasteners, vents, drains, cracks, holes, voids, splits and penetrations on most roofs. Four Seasons Reinforcing Tape provides outstanding physical strength, unique elongation, quick wet-out and saturation, and ease of application.

- Easy To Use
- Quick Saturation
- High Tensile Strength
- Long-Term Durability
- Superior Reinforcement

Property	Typical Results
Weight (per sq. yard)	3 Ounces
Bursting Strength (lbs)	177
Tensile Strength (psi)	57.1.
Tear Strength (lbs)	16.1
Elongation (%)	62
Conformability	Excellent
Ease of Saturation	Excellent

APPLICATION INSTRUCTIONS:

Three course method for applying sealant: Over a clean and prepared substrate apply either Four Seasons Acrylic Sealant or Silicone Sealant with either brush or

trowel at a rate of 20 square feet per gallon to the area to be repaired or reinforced. Immediately apply reinforcing fabric to the wet material making sure to fully embed the fabric while working out any voids or fish mouths in the fabric. Then apply another pass of Sealant at 10-15 square feet per gallon completely encapsulating the fabric with the application. The finished repair/reinforcement should be approximately 1/6th-1/8th inch in thickness. After allowing fully cure, coat with Four Seasons Roof Coating to complete application.

All surfaces must be clean, dry, and free of dirt, grease, oil, or other contaminants that would interfere with proper adhesion. Apply only when weather conditions will permit drying before rain, dew or freezing temperatures. Apply at temperatures above 50°F. For application details see specific Guide Specifications.

STORAGE - Store materials between 40°F and 100°F to prevent damage to products. Do not store at high temperatures or direct sunlight. Protect all materials from freezing during transit, handling, storage, and installation. Minimum one year shelf life if stored at 40°F-90°F.

MAINTENANCE - Periodic maintenance ensures extended performance and reduces life cycle costs.

TECHNICAL SERVICES - Additional information, product brochures, and guide specifications are available. Roof energy evaluations, life cycle cost analyses, and other roof management services are also available from a National Coatings Technical Consultant.

Available Size

Product	Product Code	Unit Size	Unit Weight
Four Seasons Polyester Reinforcing Fabric	FSRF-4	4 inch x 324 foot roll	29 lbs



NATIONAL COATINGS CORPORATION
1201 Calle Suerte Camarillo, CA 93012
800-423-9557 www.nationalcoatings.com