



FOUR SEASONS ROOF PRIMER

Four Seasons Roof Primer is a premium, multi-purpose, acrylic, elastomeric primer for use over a variety of substrates including asphalt, BUR, cap sheet, previous coatings, TPO, EPDM, SPF, concrete and metal roofing. Four Seasons 365 Roof Primer provides durability, energy savings, prolonged roof life, and reduced life cycle costs. Four Seasons 365 Acrylic Roof Primer is a dark color, low VOC primer that dries quickly and accelerates the evaporation of morning condensation to reduce topcoat application time.

- Quick dry
- Promotes maximum adhesion
- Stops bleed through
- Environmentally friendly
- Easy roll on application
- Cost effective
- Water clean-up

Property	Typical Results
Color	Charcoal
Solids Content By Volume	44% ± 2
Clean Up	Water
VOC	34g/l

INSTALLATION

For Four Seasons Acrylic Roof Coatings:

Clean all roof surfaces with Four Seasons 365 Roof Cleaner. All surfaces must be dry and free of dust, dirt, oil, loose coating, mildew, algae and all other foreign matter. Use Four Seasons 365 Peel and Stick Tape to bridge problematic seams and laps. Fill all cracks, holes, voids, splits and penetrations with Four Seasons 365 Acrylic Roof Patch & Sealant. Allow sealant to dry 12-24 hours. Using a ¾" nap roller, prime entire roof with Four Seasons 365 Roof Primer at a spread rate of 100 sq. ft. per gallon. Allow primer to dry for 4-12 hours. Proceed to apply the Four Seasons Acrylic Roof Coatings per application instructions.

For Four Seasons Silicone Roof Coatings:

Clean all roof surfaces with Four Seasons 365 Roof Cleaner. All surfaces must be dry and free of dust, dirt, oil, loose coating, mildew, algae and all other foreign matter. Using a ¾" nap roller, prime entire roof with Four Seasons 365 Roof Primer at a spread rate of 100 sq. ft. per gallon. Allow primer to dry for 4-12 hours. Use Four Seasons 365 Peel and Stick Tape to bridge problematic seams and laps. Fill all cracks, holes, voids, splits and penetrations with Four Seasons 365 Silicone Roof Patch & Sealant. Allow sealant to dry 12-24 hours. Proceed to apply the Four Seasons Silicone Roof Coatings per application instructions.

STORAGE - Store materials between 40°F and 100°F to prevent damage to products. Do not store at high temperatures or direct sunlight. Protect all materials from freezing during transit, handling, storage, and installation. Minimum one year shelf life if stored at 40°F-90°F.

MAINTENANCE - Periodic maintenance ensures extended performance and reduces life cycle costs.

TECHNICAL SERVICES - Additional information, product brochures, and guide specifications are available. Roof energy evaluations, life cycle cost analyses, and other roof management services are also available from a National Coatings Technical Consultant.

Available Sizes

Product	Product Code	Unit Size	Unit Weight	Pack
Four Seasons Roof Primer - 1 Gallon	FSRP-1	1 gal.	12 lbs	4
Four Seasons Roof Primer - 5 Gallon	FSRP-5	5gal.	58 lbs	1



NATIONAL COATINGS CORPORATION
 1201 Calle Suerte Camarillo, CA 93012
 800-423-9557 www.nationalcoatings.com