

07700 Roofing Specialties and Accessories/Roofing Granules

**NATIONAL
COATINGS**

1. PRODUCT NAME

ROOFGUARD GRANULES

Roofing Granules

2. SUPPLIED BY

NATIONAL COATINGS CORP.

1201 Calle Suerte

Camarillo, CA 93012

Phone: 800-423-9557

Fax: 800-294-3866

www.nationalcoatings.com

info@nationalcoatings.com

3. PRODUCT DESCRIPTION

ROOFGUARD ROOFING GRANULES are specifically designed for use over all substrates with high performance ACRYSHIELD® Acrylic Roof Coatings and SRC Silicone Roof Coatings and are the superior choice for SPF roofing applications. They are excellent for creating durable traction for walk pad applications.

APPROVALS:

- UL 790 Class A Rating



- ENERGY STAR® Product in white and sand meet guidelines.



- Factory Mutual Standard 4470 for Class 1 Fire, Windstorm, & Hail Classification



- CRRC Rated – Prod ID 0626-0005



- California Title 24



- Accredited by the Spray Polyurethane Foam Alliance, a business unit of the American Plastics Council



- ICC-ES ESR-2140



4. TECHNICAL DATA

See table on next page.

5. INSTALLATION

- May be applied by hand or blower.

- Broadcast at least 35 lbs. per square into 1.5 gallons per square of wet ACRYSHIELD coating.
- For application details see specific Installation Guide Specifications.

6. AVAILABILITY AND COST

ROOFGUARD GRANULES may be purchased directly from National Coatings Corporation. For information call 800-423-9557.

7. WARRANTY

Various warranties are available for ROOFGUARD GRANULES when used with specific ACRYSHIELD SPF Roofing Systems installed by approved applicators.

8. MAINTENANCE

Periodic maintenance of ACRYSHIELD SPF Roofing Systems containing ROOFGUARD GRANULES ensures extended performance and reduces life-cycle costs.

9. TECHNICAL SERVICES

Additional information, product brochures, and installation guide specifications are available from National Coatings Corporation.

10. FILING SERVICES

Additional product information is available from National Coatings Corporation.



07700 Roofing Specialties and Accessories/Roofing Granules



TECHNICAL DATA

Properties	Average Value
Bag Net Weight	80 lbs.
Number of Bags/Pallet	35 – 2,800 lbs.
Truckload	15 - 18 pallets
Color	Bright White
Bulk Density	90 – 100 lbs/cu ft
Particle Size	1 – 2mm

These products are for industrial/commercial applications only. These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control.

