

# Membrane Roofing/Silicone Safety Granules



## 1. PRODUCT NAME

**SRC<sup>SM</sup> Safety Granules**  
Silicone Safety Yellow Walkway  
Roofing Granules

## 2. SUPPLIER

**NATIONAL COATINGS CORP.**  
1201 Calle Suerte  
Camarillo, CA 93012  
Phone: 800-423-9557  
FAX: 800-294-3866  
www.nationalcoatings.com

## 3. PRODUCT DESCRIPTION

**SRC SAFETY GRANULES** enhance the impact resistance of the roof surface and also provide a non-skid walking surface when embedded in **SRC SAFETY COATING**.

**SRC SAFETY GRANULES** provide high-performance UV resistance for outdoor applications. Only the most UV stable pigments have been incorporated into the product to maintain colorfastness.

## BENEFITS:

- *Non-Skid Surface*
- *High Reflectivity*
- *Impact Resistance*
- *Advanced UV Protection*
- *Saves Energy*
- *Extends Roof Life*

## 4. TECHNICAL DATA

See table below.

## 5. INSTALLATION

- Immediately after the application of SRC Safety Coating, evenly broadcast the SRC Safety Granules into the wet coating.
- For application details see specific Guide Specifications.

## 6. STORAGE

Recommended shelf life of five (5) years when stored in dry environments.

## 7. AVAILABILITY AND COST

**SRC SAFETY GRANULES** may be purchased directly from National

Coatings Corporation. For information call 800-423-9557.

## 8. WARRANTY

Various warranties are available for specific SYSTEMS installed by approved applicators.

## 9. MAINTENANCE

Periodic maintenance ensures extended performance and reduces life cycle costs.

## 10. TECHNICAL SERVICES

Additional information, product brochures, and guide specifications are available. Roof energy evaluations, life cycle cost analyses, and other roof management services are also available from a National Coatings Technical Consultant.

## 11. FILING SERVICES

Additional product information is available from National Coatings Corporation.

## Technical Data

Property	Typical Results
Hardness (Moh's Hardness Scale)	6.5 – 7.0
Bulk Density (ASTM C29/C29M-97)	90-100 lbs./cu. ft.
Specific Gravity (ASTM C128-01e1)	2.65

Composition	Results
Silica Sand	97.5%
Resin	2.0%
Colorants	0.5%

**SRC SAFETY GRANULES** are for industrial/commercial applications only. These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control.

