

PLUG-IN-DETECTOR BASE

DESCRIPTION

The 63-1055/63-1061, 4 inch sensor base will mount to 3 ½ inch octagon boxes, 4 inch square boxes with plaster rings, and European boxes with 50, 60, and 70 mm screw spacing. This base is approximately the same size as the sensor head. It is to be used with any of the CyberCat/Cheetah Xi sensors. The remote LED connection is fully programmable.



SPECIFICATIONS

Diameter: 6.1 inches (155 mm);
 63-1054/63-1061 4.0 inches (102 mm)

Wire Gauge: 12 to 18 AWG (0.9 to 3.25 mm²)

ORDERING INFORMATION

Fike P/N	Manf. Model No.	Description
Mounting Bases		
63-1055		4" Flangeless Mounting Base - Non-isolator
63-1061		4" Flangeless Mounting Base - Isolator
Accessories		
20-1085	F110	Retrofit Flange
02-3868	RA400Z	Remote LED Annunciator
20-1087	XR2B	Detector Removal Tool (20-1089 included)
02-4986	XP-4	Extension for 02-4985 (5–15 ft)
20-1089	T55-127-000	Detector Removal Head
20-1090	BCL-20B	Black Detector Kit
55-051		Configuration IR Tool
Compatible Sensors		
63-1052		Photo - Non-isolator
63-1058		Photo - Isolator
63-1053		Photo/Heat - Non-isolator
63-1059		Photo/Heat - Isolator
60-1039		Heat - Non-isolator
60-1040		Heat - Isolator
67-033		Ion - Non-Isolator
67-034		Ion - Isolator

APPROVALS

- UL - S911
- FM - 302 1590
- MEA - 9-05-E
- CSFM - 7300-0900:138

Form No. P.1.99.01-1

(This page is left blank intentionally)

