

Fenwal Engineered Fire Suppression System

Effective March 2005

F-44-5150

Designed for use with 3M™ Novec™ 1230 Fire Protection Fluid


4" Stop (Directional) Valve Component Sheet

FENWAL®

P/N: 890208

FEATURES

- For use with UL Listed, ULC Listed and FM Approved Systems



Note:

1. Valve must be installed with the arrow pointing in the direction of flow.
2. Equivalent length = 206 ft. (63 m).

MATERIALS

- Valve Body: Brass
- Gasket: Iron
- Flanges, Bolts and Nuts: Steel

Fenwal is a registered trademark of Kidde-Fenwal, Inc.

3M and Novec are trademarks of 3M.

All other trademarks are property of their respective owners.



FENWAL®

Protection Systems

KIDDE-FENWAL, INC.
400 MAIN STREET, ASHLAND, MA 01721
TEL: (508)881-2000 FAX: (508) 881-8920
www.fenwalfire.com

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to perform as described herein. If you need more information on this product, or if you have a question, contact KIDDE-FENWAL, INC., Ashland, MA 01721; Telephone (508) 881-2000