

PLUG-IN DETECTOR BASE

DESCRIPTION

The 63-1054/63-1060, 6 inch sensor base will mount directly to 3 1/2 inch and 4 inch octagon boxes, 4 inch square boxes (with or without plaster rings) and single gang boxes. This base is approximately 2 inches larger than the sensor, providing a contouring effect and covering junction box. It is to be used with any of the CyberCat/Cheetah Xi sensors. The remote LED connection is fully programmable



SPECIFICATIONS

Diameter: 6.1 inches (155 mm);
 63-1054/63-1061 4.0 inches (102 mm)

Wire Gauge: 12 to 18 AWG (0.9 to 3.25 mm²)

ORDERING INFORMATION

Fike P/N	Manf. Model No.	Description
Mounting Bases		
63-1054		6" Flangeless Mounting Base - Non-isolator
63-1060		6" Flangeless Mounting Base - Isolator
Accessories		
20-1085	F110	Retrofit Flange
02-3868	RA400Z	Remote LED Annunciator
20-1087	XR2B	Detector Removal Tool (20-1089 included)
02-4986	XP-4	Extension for 02-4985 (5-15 ft)
20-1089	T55-127-000	Detector Removal Head
20-1090	BCL-20B	Black Detector Kit
55-051		Configuration IR Tool
Compatible Sensors		
63-1052		Photo - Non-isolator
63-1058		Photo - Isolator
63-1053		Photo/Heat - Non-isolator
63-1059		Photo/Heat - Isolator
60-1039		Heat - Non-isolator
60-1040		Heat - Isolator
67-033		Ion - Non-Isolator
67-034		Ion - Isolator

APPROVALS

- UL - S911
- FM - 3021590 (non-isolator) 3023166 (isolator)
- MEA - 9-05-E
- CSFM - 7300-0900:138

Form No. P.1.98.01-1

(This page is left blank intentionally)

