

DUCT DETECTOR REMOTE ACCESSORIES

DESCRIPTION

The NS Duct Detector Remote Accessories are designed to be used with the Conventional and Analog Duct Detectors to provide audible and visual indication as well as remote test/reset functions.

These devices are constructed of brushed stainless steel and mount on a standard single or double gang backbox.

SPECIFICATIONS

Power Requirements (provided by Duct Detector)

Alarm LED	15 ma
Pilot LED	15 ma
Horn	20 ma @ 24 VDC

Sound Pressure

Horn	78 db @ 10 feet
------	-----------------

Dimensions

Single Gang	2.75" (69.85mm) W
	4.5" (114.3mm) H
Double Gang	4.5" (114.3mm) W
	4.5" (114.3mm) H

Fike P/N 63-034 (MS-RA)

Function:

Remote Alarm LED (red)

For use with:

63-030, 67-029, 63-031, 67-030, 63-028, 63-029

Fike P/N 63-036 (MS-KA/R)

Function:

Remote Alarm LED (red)

Key-Operated Test/Reset Switch

For use with:

63-030, 67-029, 63-031, 67-030, 63-029

Fike P/N 63-035 (MS-RA/P)

Function:

Remote Alarm LED (red)

Pilot LED (green)

For use with:

63-030, 67-029, 63-031, 67-030, 63-029

Fike P/N 63-037 (MS-KA/P/R)

Function:

Remote Alarm LED (red)

Pilot LED (green)

Key-Operated Test/Reset Switch

For use with:

63-030, 67-029, 63-031, 67-030, 63-029

Fike P/N 63-038 (MS-RH/KA/P/R)

Function:

Remote Alarm Horn

Remote Alarm LED (red)

Pilot LED (green)

Key-Operated Test/Reset Switch

For use with:

63-030, 67-029, 63-031, 67-030

(This page is left blank intentionally)

