



## PRELIMINARY PRODUCT DATA SHEET



### Hyperspec<sup>®</sup> MV.X

Rugged Hyperspectral  
Machine-Vision Camera with  
Onboard Data Processing

- Visualize value at the speed of light
- Classify and detect using the spectral dimension
- Embedded hyperspectral classification made intuitive, reliable, and fast
- Industry first onboard data processing with an IP67-rated housing
- Integrated solutions include camera, software, illumination, processing equipment interface

# PRODUCT DATA SHEET

## PRELIMINARY



The Headwall MV.X brings hyperspectral imaging to machine-vision applications that have previously been too demanding for an off-the-shelf solution. Challenges such as liquids, dust, and the sheer amount of raw data generated by hyperspectral data acquisition have been overcome.

An industry-first IP67 enclosure contains Headwall's unrivaled aberration-corrected concentric spectrograph design, high-performance CMOS focal-plane array, and onboard processing to output not gigabytes of raw data but spectrally classified images that can be used in real time for rapid product grading & inspection along your processing line.

Hyperspec® MV.X	
Wavelength range (nm)	400-1000
Spatial bands	1024
Spectral bands	342
Spectral sampling (nm/pixel)	1.75
Spectral FWHM (nm)	6
System F-Number	2.5
Optical design	Aberration-corrected concentric
Angular field of view 24mm lens (deg), other lenses available	14
Instantaneous field of view 24mm lens (deg), other lenses available	0.014
Bit depth	12
Interface	GenICam-compliant GigE
Software	Web user interface for system configuration and control; onboard, in-camera classification modules available
Camera sensor technology	CMOS
RAM / Solid-State Storage (GB)	8GB RAM, 128GB SSD
Max power consumption (W)	< 45W
Dimensions (L x W X H, in/mm)	8.9 x 5.1 x 5.1 / 225 x 130 x 130
Weight with 24mm lens (lb / kg)	8.8 / 4
Ingress Protection (IP) rating	IP67
Operating Temperature	0 °C to 50 °C



January 2020

© 2020 Headwall Photonics, Inc. Information in this document is subject to change without notice. Headwall Photonics, Inc. reserves the right to change or improve its products and specifications and to make changes in content without obligation to notify any person or organization of such changes or improvements. The Hyperspec® name (and all its derivations) is a registered Trademark of Headwall Photonics, Inc. \*US and/or EU Export Restrictions may apply to this Dual Use Product.

contact information  
 Headwall Photonics, Inc.  
 580 Main Street • Bolton, Massachusetts 01740  
 978-353-4100  
 information@headwallphotonics.com