

3M Soft aluminium adhesive tapes 1436 P/F

Economical alternative for simple applications

Application:

For sealing and insulation in the construction industry and in air conditioning technology.

Notes:

We recommend that you request the safety data sheet with your first order.

Execution:

- With an easy-to-remove protective cover

Advantage:

- Good adhesion to a wide variety of surfaces
- Protective cover enables punched pieces to be produced
- Flame retardant according to DIN 4102 B1

Technical data:

- Thickness: 0.075 mm
- Colour: Silver
- Type of adhesive: Rubber/resin
- Min./max. temperature resistance: -25 to 70 °C
- Max. short-term temperature resistance: 100 °C
- Breaking elongation: 3 %



Width of tape x length of strap	50 mm x 50 m	75 mm x 50 m
69771... Ident. No.	385	395

Prod. Gr. 6RM

3M Soft aluminium adhesive tapes 431

Suitable for long-term applications

Application:

For sealing, for heat and light reflection, for covering of surfaces for aluminium anodising and as a moisture barrier.

Notes:


We recommend you request the safety data sheet with your first order.

Advantage:

- High ageing stability
- Good resistance to chemicals
- Strong heat and light reflection
- Low flammability (class L)

Technical data:

- Type description: 431
- Thickness: 0.09 mm
- Colour: Silver grey
- Type of adhesive: Acrylate
- Adhesive tape backing material: Soft aluminium
- Min./max. temperature resistance: -55 to 155 °C
- Breaking elongation: 5 %



Width of tape x length of strap	25.0 mm x 55 m	50 mm x 55 m
69771... Ident. No.	380	390

Prod. Gr. 6RM

3M Multi-purpose soft PVC tape 764i

For marking, bundling, holding, sealing

Execution:

- Soft to the touch and elastic, with high adhesive strength

Advantage:

- High initial adhesive strength
- High adaptability
- Good resistance to solvents
- Very easy to use, even on uneven surfaces
- Very easy to use, even on uneven surfaces

Notes:

We recommend that you request the safety data sheet with your first order.

Technical data:

- Width of tape x length of strap: 50.8 mm x 33 m
- Thickness: 0.125 mm
- Type of adhesive: Rubber/resin
- Adhesive tape backing material: Soft-PVC
- Breaking elongation: 180 %



Ident. No. 550



Ident. No. 555



Ident. No. 560



Ident. No. 565

Colour	Blue	White	Orange	Red
69772... Ident. No.	550	555	560	565

Prod. Gr. 6RM

3M Temflex™ PVC electrical insulating tapes (EN standard DIN EN 60454-3-1)
 Ideal for insulating, bundling, fastening and coloured marking

Advantage:

- Self-adhesive
- Highly elastic
- Good electrical and mechanical properties



Ident. No. 205, 220, 235



Ident. No. 210, 225, 240



Ident. No. 215, 230, 245

Colour	Width of tape x length of strap Breaking elongation (%)	15 mm x 25 m		15 mm x 10 m		19 mm x 25 m	
		69772... Ident. No.	●	69772... Ident. No.	●	69772... Ident. No.	●
Black	170	205	●	220	●	235	●
Blue	170	210	●	225	●	240	●
Green Yellow	170	215	●	230	●	245	●

Prod. Gr. 6RM



3M Scotch® PP packaging adhesive tapes 305
For light cardboard packaging and film packaging

Execution:

- Limited UV resistance
- With FDA approval

Advantage:

- Unrolls quietly

Notes:

We recommend that you request the safety data sheet with your first order.

Technical data:

- Width of tape x length of strap: 50 mm x 66 m
- Thickness: 0.043 mm
- Type of adhesive: Acrylate
- Adhesive tape backing material: Bi-axial stretched PP film



Colour		Brown	Transparent
69772...	Ident. No.	470	475

Prod. Gr. 6RM

3M Scotch® PVC packaging adhesive tapes 6890
High-quality, low-noise packaging tape

Execution:

- Humidity-resistant and resistant to chemicals

Advantage:

- Silent unrolling
- Can be torn off by hand

Notes:

We recommend you request the safety data sheet with your first order.

Technical data:

- Width of tape x length of strap: 50 mm x 66 m
- Thickness: 0.05 mm
- Type of adhesive: Natural rubber
- Adhesive tape backing material: PVC
- Breaking elongation: 75 %



Ident. No. 485



Ident. No. 490

Colour		Brown	Transparent
69772...	Ident. No.	485	490

Prod. Gr. 6RM

3M soft PVC adhesive tapes
for indoor use

Application:

For marking, barricading, bundling, protecting and covering. Also suitable for making the floor. Ideal for indicating hazards.

Execution:


- Highly elastic backing material

Advantage:

- Solvent-resistant
- High initial adhesive strength
- Supple even on uneven surfaces

Notes:

We recommend you request the safety data sheet with your first order.



Ident. No. 505



Ident. No. 515

Type description		766i	767i
Width of tape x length of strap		50 mm x 33 m	50 mm x 33 m
Colour		Black Yellow	Red White
Breaking elongation (%)		180	180
69772...	Ident. No.	505	515

Prod. Gr. 6RM

Extremely robust hand dispenser for adhesive tapes

Ideal for continuous use

Application:

For use with packaging adhesive tapes with a length of up to 66 m and width of 50 mm.

Execution:

- With notch trigger
- Two pressure rollers
- Extremely robust



69772...	Ident. No.	601
----------	------------	-----

Prod. Gr. 686

3M Double-sided, transparent adhesive tapes 9088-200

For all kinds of mounting tasks

Application:

For self-adhesive fitting of furniture boards, cable ducts or sealing profiles. Also suitable for mounting, assembling and fixing advertising materials.

Notes:

We recommend that you request the safety data sheet with your first order.



Advantage:

- High UV and temperature resistance
- Excellent shear strength
- Backing for easier handling and use

Technical data:

- Thickness: 0.2 mm
- Type of adhesive: Modified acrylate
- Adhesive tape backing material: PET foil
- Max. short-term temperature resistance: 150 °C
- Material to be processed: Metal | Glass | ABS | PVC | Cardboard | PET | Polycarbonate | Polypropylene | Polystyrene | Powder-coated surfaces

Width of tape x length of strap	19 mm x 50 m	25 mm x 50 m	38 mm x 50 m	50 mm x 50 m	
69771...	Ident. No.	270	272	274	276

Prod. Gr. 6RM

Pica Gel signal marker

for universal use

Application:

For permanent markings on all materials, both indoors and outdoors.

- Fast-drying
- Light- and weather-resistant
- Temperature-resistant up to 1000°C

Execution:

- Chloride-free; therefore ideal for marks on stainless steel
- Variable line thickness, approx. 2-8 mm

Technical data:

- Material to be processed: Rubber | Ceramics | Tiling | Glass | Plastic | Wood | Steel | Stainless steel | Leather

Advantage:

- Highly permanent



Ident. No. 310

Ident. No. 320

Ident. No. 330

Ident. No. 340

Colour	White	Red	Blue	Yellow	
69794...	Ident. No.	310	320	330	340

Prod. Gr. 650

Markal MARKAL Quik Stik mini marker

Compact solid-colour pen

Application:

Ideal for finer line markings on smooth or rough surfaces

Advantage:

- Marks virtually any surface, whether it is wet, smooth, rough or hot
- Leaves strong, durable marks on almost any surface

Execution:

- Fast-drying
- Light- and weather-resistant
- With no xylene or ethylene glycol monobutyl ether

Technical data:

- Line thickness: 6 mm
- Material to be processed: Steel | Iron | Glass | Wood | Rubber | Ceramics | Plastic



Ident. No. 200

Ident. No. 203

Ident. No. 205

Ident. No. 207