



Water hose reel

Reel body made of special shatter-proof plastic

Execution:

- Highly elastic, hard-wearing special hose with textile lining and spiral-wrapped canvas
- With quick hose connector, water stop and adjustable spray nozzle made of plastic
- Carrier frame made from galvanised steel tube

Technical data:

- Hose length: 20 m
- Drum body material: Plastic
- Hose inner diameter in inches: 1/2 in
- Diameter: 320 mm
- Width x height x depth: 415 x 315 x 205 mm
- Weight: 4.85 kg



75014...

Ident. No.

030

Prod. Gr. 750

High pressure washer – unheated and heated

Voltage 230 V, 50 Hz, shockproof, suppressed

Application:

For powerful cleaning outdoors with extremely stubborn contamination.

Execution:

- Mobile entry-level model
- High-quality brass cylinder head
- With fine water filter
- Vertical and horizontal operation possible

Advantage:

- Integrated carrying handle allows easy loading and comfortable transport
- Automatic pressure relief protects components and increases service life

Delivery:

15-m high-pressure hose, stainless steel pipe, high-pressure gun, dirt blaster, triple nozzle

Technical data:

- Model: HD 6/13 C plus
- Heated: No
- With hose reel: No
- Power input: 2700 W
- Min. feed quantity: 230 l/h
- Max. feed quantity: 560 l/h
- Min. pressure: 30 bar
- Max. pressure: 130 bar
- Max. inlet temperature: 60 °C
- Length x width x height: 360 x 375 x 925 mm
- Weight: 23.0 kg

75730...

Ident. No.

127
(O)

Prod. Gr. 7NK

Sweeping machines

for interior and exterior cleaning

Application:

ideal choice for cleaning small production facilities, car parks, shopping centres, schools, workshops, bus and railway stations as well as in outdoor areas of office buildings.

Execution:

- with 2 side brushes
- metal drive on both sides for equally excellent sweeping performance when making left and right turns
- push handle foldable and adjustable in 3 different heights

- with dust filter for a clean exhaust air while sweeping
- Working width 480 mm, not including lateral brushes

Advantage:

- cleaning is up to 6 times faster than when using a normal broom.
- virtually maintenance-free: a simple mechanical construction. no motor and no battery.
- easy to control thanks to large wheels

Delivery:

main sweeping roller, 2 side brooms, folding handle



Model	KM 70/20 C S2B
Max. working width (mm)	960
Container capacity (l)	42
Max. surface coverage per hour (m²)	3680
Length x width x height	1300 x 960 x 1050 mm
Weight (kg)	26

75730...

Ident. No.

151

Prod. Gr. 7NK

Floor cleaning machine BR 30/4 C Adv

Application:

For manual cleaning of hard surfaces from 20 to 200 m². Ideal for cleaning smaller shops, restaurants, petrol stations, supermarkets, sanitary areas, snack areas of hotels.

Execution:

- Scrubber-dryer with microfibre roller intended for cleaning stoneware tiles
- Manual suction tube for cleaning inaccessible corners

Advantage:

- No risk of slippage – the floor is immediately dry after cleaning and can be walked on

- Works forwards and backwards

Delivery:

With roller brush, suction lips, integrated suction pipe

Technical data:

- Model: BR 30/40 C Adv
- Max. working width: 300 mm
- Container capacity: 4 l
- Max. surface coverage per hour: 200 m²
- Length x width x height: 390 x 335 x 1180 mm
- Weight: 12.4 kg



75730...

Ident. No.

101
O

Prod. Gr. 7NK

Source: Hahn+Kolb Werkzeuge GmbH

Technical data subject to change.

Availability subject to country specific rules and regulations.

www.iconridge.com

Model Kärcher BR 30/4 C Adv

Nilfisk Wet/dry vacuum cleaners ALTO for use in workshops and industry

Application:

No. 75520: handy and robust vacuum cleaner – ideal for small cleaning tasks in workshops

No. 75521 042: Multi-purpose vacuum cleaner for industry and skilled trades.

No. 75521 051: Multi-purpose vacuum cleaner for crafts, industry and professionals.

Execution:

▪ **No. 75520:** Blow-out function

▪ **No. 75521 042:** with cable and accessory holder

Advantage:

▪ washable PET filter element

▪ **No. 75521 042:** suction regulation on hand-held tube

Delivery:

No. 75520: 19-m suction hose (dia. 32 mm), hand-held tube with suction regulation, extension tube, joint and floor nozzle, universal nozzle, filter element and fleece filter bag

No. 75521 042: suction hose D32 x 3.5 m, aluminium extension pipes D36 2 x 500 mm, floor nozzle, joint nozzle, PET filter element Ø 185 x 140 mm, filter bag

No. 75521 051: With suction hose (diameter 32 mm), hand tube, aluminium extension tube, combination floor nozzle, joint nozzle, non-woven fabric filter bag and tool adapter

Model	21-01 PC INOX	ATTIX 30-01	ATTIX 30-21
Power input (W)	1250	1500	1500
Max. air delivery volume (l/min)	3600	3700	3700
Underpressure (mbar)	210	250	250
Container capacity (l)	20	30	30
Sound-pressure level (dB)	64	59	59
Weight (kg)	8.5	10	10.0
Cable length (m)	5.0	7.5	7.5
Filter cleaning	Semi-automated	-	Semi-automated
With device connector	No	No	Yes
With antistatic system	No	No	Yes
With automatic shut off	No	No	-
With accessory tray	Yes	Yes	Yes
With soft start	No	No	Yes
Material of the bins	Stainless steel	-	Plastic
With speed control	No	No	Yes
Length x width x height	390 x 400 x 525 mm	450 x 380 x 595 mm	450 x 380 x 595 mm
75520...	Ident. No. 012	-	-
75521...	Ident. No. -	042	051

Prod. Gr. 759

Accessories for		75520 012	75521 042	75521 051
75520... Filter bag Aero set 4+1 (4 fleece filters + 1 wet filter)	Ident. No.	311	-	-
75521... Fleece filter element, dia. 185x140 mm, M-class	Ident. No.	440	440	440
75521... Fleece filter bag (pack of 5)	Ident. No.	-	341	341

Nilfisk Wet/dry vacuum cleaners ALTO for professional applications

Application:

No. 75522: for professional use in wet and dry applications

No. 75524: flexible high-performance vacuum cleaner with two-motor drive (2x 1500 W) for demanding cleaning tasks.

Execution:

▪ **No. 75524:** tilting and removable container

Advantage:

▪ washable PET fleece filter element

▪ **No. 75522:** high vacuum performance with low noise levels

Delivery:

No. 75522: 4-m suction hose (diameter 36 mm), rubber diagonal tube nozzle, curved hand-held tube, filter element and fleece filter bag

No. 75524: 4-m suction hose (38 mm), 2 x 0.5-m stainless steel extension tube, bent hand pipe, fleece filter bag and PET nano fibre filter element, 400-mm floor nozzle, 300-mm plastic joint nozzle

Model	ATTIX 751-11	ATTIX 961-01
Power input (W)	1500	1500
Max. air delivery volume (l/min)	3600	3600
Underpressure (mbar)	230	250
Container capacity (l)	70	70
Sound-pressure level (dB)	57	67
Weight (kg)	25.0	30.0
Cable length (m)	7.5	10.0
Filter cleaning	-	Semi-automated
With device connector	Yes	No
With antistatic system	Yes	No
With accessory tray	Yes	Yes
With soft start	Yes	Yes
Material of the bins	Stainless steel	Stainless steel
Length x width x height	605 x 580 x 970 mm	580 x 600 x 970 mm
75522...	Ident. No. 036	-
75524...	Ident. No. -	020

Prod. Gr. 759



No. 75520



No. 75521 042



No. 75522



No. 75524

Accessories for		75522 036	75524 020
75521...	Chip set: 1 suction hose (dia. 50 mm, 4 m), 1 rubber diagonal pipe nozzle (260 mm) for ATTIX 961-01 and ATTIX 751-11	Ident. No. 110	110
75521...	Filter bags, 5 units	Ident. No. 360	-
75521...	Fleece filter element, dia. 185x140 mm, M-class	Ident. No. 440	-
75521...	Chip basket for ATTIX 961-01	Ident. No. -	120
75521...	Fleece filter bags PU (pack of 5)	Ident. No. -	365
75521...	Filter element	Ident. No. -	460

Wet/dry vacuum cleaners for professional applications

Application:

No. 75523: for removing large quantities of fine dust, but also for coarse dirt and water. Ideal for use in construction, the food sector, the automotive branch and in industry in general.

No. 75526: for universal commercial use.

Execution:

- Maintenance-free suction turbines
- **No. 75523:**
 - discharge hose (oil resistant)
 - tilting frame
 - stop castor
- **No. 75526:** mechanical float cut-off

Advantage:

- **No. 75523:**
 - two motors for consistently high suction power

- filter cleans itself with targeted, powerful blasts of air. The process is triggered automatically and the suction power remains consistently high. Further advantages: low maintenance costs, long filter service life.

- adjustable push handle and large wheels ensure easy transport to the site, even on uneven surfaces.

Delivery:

No. 75523: 4.0-m suction hose, C 40 with elbow, electrostatically earthed, 2 x 0.5-m metal suction tubes, wet/dry suction nozzle (360 mm), joint nozzle, flat folding filter

No. 75526: With 2.5-m suction hose with elbow, cartridge filter, metal suction hose 2 x 0.5 m, wet and dry floor nozzle, joint nozzle, paper filter bag (double layered, BIA C)

Model	NT 27 / 1 ME Advance	NT 65 / 2 Tact 2
Power input (W)	1380	2760
Max. air delivery volume (l/min)	4020	4440
Underpressure (mbar)	208	254
Container capacity (l)	27	65
Sound-pressure level (dB)	72	73
Weight (kg)	8.2	24.5
Cable length (m)	7.5	10.0
With device connector	No	No
With antistatic system	No	Yes
With automatic shut off	No	Yes
With accessory tray	No	Yes
Material of the bins	Stainless steel	Plastic
Length x width x height	420 x 420 x 540 mm	575 x 490 x 880 mm
Protection class	Protection class II/protective insulation	Protection class I/protective grounding
75526...	Ident. No. 023	-
75523...	Ident. No. -	017

Prod. Gr. 7NK

Accessories for		75523 017	75526 023
75523...	Paper filter bags, dust class M, three ply, (pack of 5)	Ident. No. 315	-
75523...	Flat folding paper filter, dust class M, nano-coated	Ident. No. 420	-
75525...	Fleece filter bags 35L, (pack of 5)	Ident. No. -	421
75526...	Paper cartridge filters (NT 27 / 1, NT 48 / 1)	Ident. No. -	422



No. 75526



No. 75523



Application:

No. 75540 000: For vacuuming: swarf, very hot swarf and plastic shavings, liquids, oils, emulsions and sludge, granulate material and small quantities of dust. ideal for cleaning machines.

No. 75540 005: For industrial application especially for vacuuming metal chips, granules, liquids, oils, slurry and dust, for cleaning machines, systems and production sites as well as for replacing coolants.

No. 75540 010: Especially suitable for vacuuming up metal chips, granules, coolants and slurry as well as leaked oil from machine tools, and for cleaning tool-changing areas and workpieces.

No. 75541: For removing large amounts of fine dust as well as coarse dirt and water in construction, foods sector, automotive segment or industry.

Execution:

No. 75540 000:

- sound-damped and splash-proof W1E-N drive unit
- nozzle holder

No. 75540 005-75540 010:

- Service life of carbon brushes approximately 2500 operating hours
- With bearing shaft for tilt emptying
- Drive unit W 2 G is sound-damped and splash-proof
- With nozzle holder

No. 75541:

- With 2 motors for constant high suction power
- With fully automatic filter cleaning
- Chassis with set down function for easy emptying of the container
- Filling level monitor with automatic shut-off
- Antistatic system

- Electrostatically earthed suction hose

Advantage:

- **No. 75540 000:** conforms to the basic safety and health requirements of EC guidelines (CE declaration of conformity)

No. 75540 005-75540 010:

- Conforms to the basic safety and health requirements of EC guidelines (CE declaration of conformity)
- The removable hose swivelling through 360° allows convenient emptying of liquids and is used as a visual fill level monitor

No. 75540 010:

- With ergonomic control handle
- Filling level display hose with chip pre-filter
- Quick connector for fast emptying

Delivery:

No. 75540 000: drive unit W1E-N, high-performance bypass suction turbine, overfilling protection and integrated safety filter, baffle plate to protect the filter, collection container made from painted sheet steel, fill level control hose and emptying hose, nozzle holder, running wheels and steering rollers with locking device

No. 75540 005-75540 010: Drive unit has 2 x 1.0 kW high-performance bypass suction turbines and integrated safety filter, steel collection container, corner screen, fill level and emptying hose, connection cable with plug, rubber-wheeled chassis made from steel, 2 lockable castors and 2 block rollers, 1 unit each of nos. 75540-105, 110 and 130

No. 75541: Suction hose 4 m, metal suction tube 2 x 0.5 m, wet/dry floor nozzle 360 mm, joint nozzle, flat folded paper filter



No. 75540 000



No. 75540 005



No. 75540 010



No. 75541

Model		RI 020 W1E-N	RI 100 W2G	RI 300 W2G	NT 55/2 Tact ² ME I
Power input (W)		1300	2000	2000	1380
Max. air delivery volume (l/min)		-	6000	6000	4440
Underpressure (mbar)		-	220	220	230
Container capacity (l)		40	80	125	55
Cable length (m)		6.0	5.0	5.0	10.0
Hose length (m)		-	3	3	4
Inner hose Ø (mm)		-	51	51	40
Length x width x height		711 x 523 x 960 mm	740 x 620 x 1180 mm	750 x 700 x 1420 mm	710 x 570 x 1070 mm
Weight (kg)		37	74.0	84.0	44.8
75540...	Ident. No.	000	005	010	-
75541...	Ident. No.	-	-	-	010 (○)*

KAERCHER = Prod. Gr. 7NK
RINGER = Prod. Gr. 760

Application:

No. 78010: For marking metal and steel with oscillating electrode.

No. 78025: For marking metal, steel and non-metallic materials with oscillating electrode.

Execution:

- Frequency 50-60 Hz
- Not suitable for anodised parts
- Suitable for thicker writing
- For 6 writing widths
- Operates with an oscillating electrode according to the electric arc short circuit principle

- Consisting of special transformer for 1-8 V secondary voltage, with on/off switch, indicator lamp, approx. 1 m connection cable with Schuko plug, writing pencil, 3 electrodes each for 1.2 x 25 mm and 1.5 x 25 mm, for steel and metals, baseplate and wooden box.
- Surface must be grease free, without rust, scale or other contamination!

Advantage:

- **No. 78025:** With intensity controller, branding pencil and 3 electrodes (hot loops)

Suitable for		Steel Metal	Steel Metal Nonferrous
Power input (W)		50	50
78010...	Ident. No.	010	-
78025...	Ident. No.	-	010

Prod. Gr. 794

Source: Hahn+Kolb Werkzeuge GmbH
Technical data subject to change.
Availability subject to country specific rules and regulations.

www.iconridge.com

