

DuoBoard

CP Series Interactive Flat Panel

Professional display solution for optimum performance



Models	CP6501K	CP8601K
Panel		
Screen Size	65"	86"
Backlight / Lightsource	DLED	DLED
Resolution (Pixels)	UHD 3840x2160 pixels	UHD 3840x2160 pixels
Brightness (Typical)	320 nits	350 nits
Contrast Ratio (Typical)	5000:1	1,200:1
Viewing Angle (Horizontal/Vertical)	178°/178°	178°/178°
Response Time (ms)	8ms	8ms
Color Gamut (x% NTSC)	72%	72%
Light Life (Typical)	30,000 hours	30,000 hours
Display Orientation	Landscape / Portrait	Landscape
Glass		
Tempered Glass	3mm, Tempered Glass	3mm, Tempered Glass
Anti-Glare & Germ-Resistant Screen	Yes	Yes
Touch		
Touch Technology	PCAP Direct Bonding	PCAP Direct Bonding
Numbers of Touch / Resolution	Up to 20 points Multi-touch	Up to 20 Point Multi-touch
Touch Interface	USB B Touch Port x2	USB B Touch Port x2
Connectivity & Sensor		
Connector	VGA x1, HDMI 2.0 x3, HDMI Out x1, 3.5mm Audio Line in/Mic in x1, 3.5mm Audio Line out x1, SPDIF Audio Out x1, USB 2.0 x3, USB 3.0 x3, USB B Touch Port x2, RS232 x1, RJ45 x1, OPS Slot x1, WiFi Module Slot (USB 2.0) x1	VGA x1, HDMI 2.0 x3, HDMI Out x1, 3.5mm Audio Line in/Mic in x1, 3.5mm Audio Line out x1, SPDIF Audio Out x1, USB 2.0 x3, USB 3.0 x3, USB B Touch Port x2, RS232 x1, RJ45 x1, OPS Slot x1, WiFi Module Slot (USB 2.0) x1
Built-in Camera	FHD Camera x1	FHD Camera x1
Built-in Microphone	Array Microphone x6	Array Microphone x6
Built-in speaker	Speakers 16W x2 & Subwoofer 15W x1 (HIFI 2.1)	Speakers 16W x2 & Subwoofer 15W x1 (HIFI 2.1)
Sensor	NFC Sensor x1, Motion Sensor x1, Air Quality Sensor x1, Light Sensor x1, IR sensor x1	NFC Sensor x1, Motion Sensor x1, Air Quality Sensor x1, Light Sensor x1, IR sensor x1
Power		
Voltage	AC 100-240V~ 50/60Hz	AC 100-240V~ 50/60Hz
Typical (Watt)	210W	350W
Mechanical		
Weight (Without / With Packing)	99.2 lbs (45kg) / 125.7 lbs (57kg ± 1.5Kg)	155 lbs (70.6kg) / 205.5 lbs (90.4kg ± 1.5Kg)
Dimension (WxHxD)	59 x 36 x 3.35in (1502.7 x 877.8 x 85.2mm)	77 x 46 x 3.35in (1962 x 1136 x 85mm)
Wall Mounting (VESA) (mm)	4 holes (600 x 400mm) Screw M8 x25mm	4 holes (800 x 600mm) Screw M8 x25mm
Handle	x2	x2
OSD		
On-Screen Display Languages	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korea / Turkey / indonesia (27L)	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korea / Turkey / indonesia (27L)
Package / Accessory		
Remote Controller	x1 (with 2.4G dongle & Battery)	x1 (with 2.4G dongle & Battery)
Power Cord	By Region	By Region
Cable	VGA(5m) x1, HDMI(1.5m) x1, Touch (3m) x1	VGA(5m) x1, HDMI(1.5m) x1, Touch (3m) x1
Quick Start Guide	x1	x1
User's Manual Electronic File	x1	x1
Touch pen	Active pen x 2pcs w/ pen holder	Active pen x 2pcs w/ pen holder
Wall Mount	x1	x1
Optional		
Optional Accessory	InstaShow, WiFi Dongle, OPS, Trolley	InstaShow, WiFi Dongle, OPS, Trolley



BenQ