





and the second of the second o

- : PANELS CAN BE PRODUCED IN:
 - : 12" AND 16" WIDTHS : LENGTHS FROM 3' TO 100'
 - : 26, 24 AND 22 GAUGE : FLAT OR WITH STRIATIONS
- : MINIMUM SLOPE AT 3:12 PITCH
- : CLIP PLACEMENT RECOMMENDED EVERY 16"
- BRIDGER STEEL RECOMMENDS STRIATIONS TO MINIMIZE OIL CANNING. BACKER ROD MAY BE APPLIED UNDER FLAT PANEL APPLICATION TO HELP MINIMIZE OIL CANNING (OIL CANNING IS NOT A CAUSE FOR REJECTION).
- : INSTALLATION OVER SOLID SUBSTRATE RECOMMENDED
- PANELS CAN BE MANUFACTURED AT JOBSITE TO GREATLY REDUCE THE RISK OF DAMAGE DURING TRANSPORTATION
- PROTECTIVE FILM CAN BE APPLIED TO PANELS FOR ADDED PROTECTION AT CUSTOMER'S REQUEST OR AT BRIDGER STEEL'S RECOMMENDATION
- MANY CUSTOM COLORS AND KYNAR PAINT SYSTEMS

 AVAILABLE IN 26, 24 AND 22 GAUGE



CUSTOMER SERVICE PROMISE:

UNEQUALED TURNAROUND TIME • INFORMATIVE/HIGHLY SKILLED STAFF

UNPARALLELED CUSTOMER SERVICE

MISSION STATEMENT:

INSPIRE THE FREEDOM TO CREATE

BRIDGER STEEL SPECIALIZES IN ARCHITECTURALLY APPEALING, UNIQUE PROFILES IN VARIOUS TYPES OF METALS INCLUDING, BUT NOT LIMITED TO, OUR RUSTIC MATERIALS TRUTEN" (A606 & 1008), GALVANIZED, GALVALUME®, BONDERIZED, REZIBOND®, AND OTHER CUSTOM METALS.



www.BridgerSteel.com • Toll Free: 877.SteelMt



