



HOSEBED CAPACITIES
 ① 300' OF 3.00" D.J. HOSE
 ② 300' OF 3.00" D.J. HOSE
 ③ 1500' OF 5.00" D.J. HOSE

STAINLESS STEEL BODY MAXIMUM O.A.L. 358.50" MAXIMUM O.A.H. 130.00" MAXIMUM O.A.W. 117.50" SIDE ROLL & FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
2. BATTERY CHARGER LOCATED IN COMPARTMENT D3
3. BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SEAT RISER
4. DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
5. ONE ADJUSTABLE SHELF IN COMPARTMENTS D1, D2, D3, P2, P3, AND R1
6. ONE ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENTS D1, AND P1
7. ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT D1, P1, AND D3
8. ONE ALUMINUM VERTICAL DIVIDER IN COMPARTMENT D3
9. CIRCUIT BREAKER PANEL IN COMPARTMENT D3
10. ONE HANNAY 1618-17-18 ELECTRIC REWIND CORD REEL IN CARGO COMPARTMENT & COMPARTMENT P3
11. AIR INLET WITH DISCONNECT COUPLING IN D5 STEP WELL

REV	DATE	BY	CH	ENFORCER
20JUN17	25MAY17	22MAY17	GVH	GHO

		JOB NO.	31125
		SCALE	1:24
TITLE 1500-D-1250 GAL POLY, 161" FH FDLR, SIDE CONTROL (2) XLYAS, HLR, LADDERS BESIDE TANK, GENERATOR		DRAWN BY	GVH
		CHECKED BY	CSH
FOR HARWINTON WEST SIDE FIRE DEPARTMENT HARWINTON, CONNECTICUT		DWG NO.	31125AD
		SHEET NO.	1 OF 1