



ALUMINUM BODY

MAXIMUM O.A.H. 132.00"

SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- RUD AUTOMATIC TIRE CHAINS
- BATTERY CHARGER LOCATED IN COMPARTMENT D3
- BATTERY CHARGE INDICATOR LOCATED AT DRIVER'S SIDE STEP AREA
- SUB-FEED CIRCUIT BREAKER PANEL IN COMPARTMENT TBD
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- ELASTIC PULL STRAP FOR DOOR ON CROSSLAY COMPARTMENTS
- ONE ADJUSTABLE SLIDE-OUT TRAY IN COMPARTMENT P1
- ONE ADJUSTABLE TILT/SLIDE-OUT FULL WIDTH/DEPTH TRAY IN COMPARTMENT P1, P2 & P3
- ONE SWING-OUT ALUMINUM TOOL BOARD IN COMPARTMENT P2
- TWO SLIDE-OUT TOOLBOARDS IN COMPARTMENT P3
- ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF LOCATED IN COMPARTMENT D2 TWO IN D1 & P3

- TRANSVERSE PARTITION IN COMPARTMENT-D1/P1
- ONE VERTICAL BOLT-IN PARTITION BETWEEN COMPARTMENTS D1-R1 & P1-R1
- STORAGE FOR LITTLE GIANT 17" LADDER IN COMPARTMENT P3
- (2) ADDITIONAL POLY TRAYS SHIPPED LOOSE
- CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- AIR INLET/OUTLET WITH DISCONNECT FITTING LOCATED ON DS PUMP PANEL
- JUMPER STUDS AT DRIVER SIDE CAB STEP
- ONE HANNAY 58E4130-17-18 ELECTRIC REWIND BOOSTER REEL WITH A CAPACITY FOR 100' OF 0.75" HOSE IN COMPARTMENT-R1 AS HIGH AS POSSIBLE
- HANNAY ELECTRIC CORD REEL MODEL (E1618-17-18) WITH CAPACITY FOR 200' OF 1/2" CABLE IN PS HATCH COMPARTMENT ABOVE P3

REV	DATE	BY	CH	DESCRIPTION
08MAY18	MMF	PJP		CHASSIS DATA
17APR18	MMF	PJP		MAKE
21MAR18	MMF	PJP		PIERCE
24JAN17	MMF	CDU		MODEL
				DAP7011

		JOB NO.	32084
		SCALE	DATE
TITLE	1500-D-750P 750 GAL WATER, 189" PUC RESCUE BODY FH/FD, (2) XLAYS, LADRS THUR BODY, DELUGE, GENRATOR	DRAWN BY	MMF
FOR	CITY OF ST. CHARLES FIRE DEPARTMENT ST. CHARLES, MISSOURI	CHECKED BY	CDU
DWG NO.	32084AD	SHEET SIZE	SHEET NO.
		D	1 OF 1