

PUMPER

BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Enforcer Chassis

CHASSIS

AXLE, FRONT, CUSTOM

18,000 Lb TAK-4 Axle

AXLE, REAR

24,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

16" Extended Stainless Steel

CAB

7010 Enforcer Cab

BODY

WATER TANK

750 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

30.75" FF RollUp Rear Compt

COMPT, PUMPER, DRIVER SIDE

152" RollUp Full Height Front & Rear FDLER

COMPT, PUMPER PASS. SIDE

152" RollUp Full Height Front & Rear FDLER

FIRE SUPPRESSION

PUMPHOUSE

48" Control Zone Side Mount

PUMP

1500 GPM Watertous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Piping For Future Husky 3/12 Foam System

Foam Cell

20 Gallon Foam Cell, Not Reduced Water

Technical drawing of a fire truck showing side, top, and rear views with dimensions and callouts for various components like lights, mirrors, and hose beds.

Side View Dimensions:

- Overall Length: 115.00 (9'-7") APPROX O.A.H.
- Running Board Hose Tray: 30" OF 5.00" HOSE
- Water Tank: 78.00
- Water Tank Width: 136.00
- Water Tank Height: 70.00
- Water Tank Depth: 19.75 CLEAR, 22.25
- Water Tank Width: 19.75 CLEAR, 22.25
- Water Tank Height: 70.00
- Water Tank Depth: 19.75 CLEAR, 22.25

Top View Dimensions:

- Overall Width: 85.00
- Water Tank Width: 70.00
- Water Tank Depth: 187.50 WB, 368.50 (30' - 8.50") APPROX OAL
- Water Tank Height: 8.00 NFPA MIN.
- Water Tank Depth: 8.00 NFPA MIN.
- Water Tank Width: 8.00 NFPA MIN.
- Water Tank Depth: 8.00 NFPA MIN.

Rear View Dimensions:

- Overall Width: 86.00
- Water Tank Width: 42.00
- Water Tank Depth: 28.00
- Water Tank Height: 16.00
- Water Tank Depth: 16.00
- Water Tank Width: 16.00
- Water Tank Depth: 16.00

Callouts:

- (1) WHELEN PIONEER L.E.D. VISOR LIGHT
- MOUNTING PROVISIONS FOR WILL-BURT NIGHT SCAN POWERLITE
- WHELEN FREEDOM IV 81" L.E.D. LIGHTBAR
- RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
- (1) WHELEN 600 L.E.D. WARNING LIGHT
- (1) WHELEN 600 L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
- (2) WHELEN 600 L.E.D. WARNING LIGHTS EACH SIDE
- (2) GROVER AIR HORNS
- (1) FEDERAL BP200-Q SPEAKER
- CENTER HOSE TRAY FOR 100' OF 1.75" HOSE
- HOSEBED CAPACITY
- BED 1: 750' OF 3.00" D.J. POLY HOSE
- BED 2: 1000' OF 5.00" D.J. POLY HOSE
- BED 3: 250' OF 3.00" D.J. POLY HOSE
- (2) HOSE BED DIVIDERS
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN M6 L.E.D. SCENE LIGHTS
- (1) 2.50" OUTLET
- PIERCE REAR VIEW CAMERA
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN 600 L.E.D. WARNING LIGHTS
- STOP/TAIL LIGHTS
- DIRECTIONAL LIGHTS
- BACK-UP LIGHTS
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING S85A
- (2) ALUMINUM PIKE POLE TUBES
- (1) BACKBOARD (2" X 18" X 72")
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- 5'-7"
- 91.00
- 72.00
- 14.00
- 28.00
- 68.00
- 40.00
- 28.00
- 96.00

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

- ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
- AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
- BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE OF THE CAB
- FOUR ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER
- TWO ALUMINUM PEGBOARDS LOCATED IN COMPARTMENTS PER SHOP ORDER

CUSTOMER APPROVAL					Pierce MANUFACTURING INC.		JOB NO.	32124	
APPROVED BY: _____					TITLE	Pierce Pumper Approval Drawing	SCALE	1:24	
DATE: _____							DATE		
				CHASSIS DATA	FOR	Pierce Stock Field Unit	DRAWN BY	COL	
				MAKE			COL	21NOV17	
				PIERCE	DWG NO.	32124AD	CHECKED BY	DJS	
				MODEL			DJS	21NOV17	
REV	DATE	BY	CH	ENFORCER	SHEET NO.				
					D				
1 OF 1									

View File Created 16-MAY-2018 07:20:26