——44.26*—* WHELEN PSL2 L.E.D. VISOR LIGHT ___ALUMINUM TREADPLATE WIFI ANTENNA — RETRAC HEATED/REMOTE MIRRORS — WITH CONVEX SECTION 129.00 (10**'**-9**"**) APPROX _____ (2) WHELEN M6 L.E.D. WARNING— 0.A.H. LIGHTS IN A COMMON BEZEL EACH SIDE STAINLESS STEEL GARNISH PLATES -Pionae 1.50" OUTLET WITH — 2.00" PIPING ---FEDERAL Q2B SIREN 19.00" EXTENDED BUMPER — (2) GROVER AIR HORNS —(2) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE EXHAUST MODIFIED FOR HYDRAULIC LADDER RACK TWIST LOCK RECEPTACLE EACH SIDE — CYLINDER PUMP ACCESS DIFFUSER SYSTEM (1) DOUBLE EXTINGUISHER COMPARTMENT -- WELDON 9186-8580-29 L.E.D. WITH STAINLESS STEEL DOOR DIRECTIONAL/MARKER LIGHT EACH SIDE ___20 GALLON FOAM CELL WHELEN SA315 SPEAKER WITH HANNAY EF24-28-29 ELECTRIC REWIND-(2) CHROME TOW HOOKS— STAINLESS STEEL GRILLE BOOSTER REEL WITH A CAPACITY FOR 200' OF 1.00" HOSE CENTER HOSE TRAY FOR 125' OF 1.75" HOSE — WITH ALUMINUM TREADPLATE NOTCHED COVER (2) CROSSLAY HOSE BEDS FOR— 200' OF 1.75" D.J. POLY HOSE WITH 2.00" PIPING MOTOR 1/3HP 33.00 _#_____ 3.00" DELUGE OUTLET WITH TFT — XG18 18.00" EXTEND-A-GUN 70.00 ________ -- SURFACE DESIGNATION AND PATHWAY MARKINGS - ALUMINUM TREADPLATE HOSE BED COVER HOSEBED CAPACITIES *** (1) 250' OF 2.50" HOSE (2) 1500' OF 4.00" HOSE (3) 500' OF 1.75" HOSE ─HUSKY 3 FOAM SYSTEM 32.44 HARRISON 6KW MSV -— FRP L.E.D. LIGHT FOR HYDRAULIC GENERATOR **---**29.50---DESIGNATED WALKWAY STORAGE COMPARTMENT FOR (1) BACKBOARD (73" X 17" X 3") HYDRAULIC LADDER RACK TO CONTAIN WITH ALUMINUM TREADPLATE DROP THE FOLLOWING EQUIPMENT: (1) 24' DUO-SAFETY 2-SEC 900-A (1) 14' DUO-SAFETY ROOF 775-A DOWN DOOR ___DIESEL EXHAUST FLUID ACCESS WITH WHELEN M9 L.E.D. SCENE — (2) WHELEN PEBP12C L.E.D. LIGHT EACH SIDE STORAGE WITH STAINLESS STEEL DOOR DECK LIGHTS MOUNTED SCENE LIGHTS WITH ALUMINUM CAB AIR CONDITIONER LEVEL INDICATOR EACH SIDE PAINTED ENCLOSURE EACH SIDE 2.50" HOSE BED OUTLET — WITH 2.50" PIPING (2) WHELEN ROTA-BEAM R316RF -(2) HOSEBED DIVIDERS L.E.D. BEACON LIGHTS WHELEN TAL65 L.E.D. TRAFFIC لجبيا STORAGE COMPARTMENT TO CONTAIN DIRECTING LIGHT RECESSED THE FOLLOWING EQUIPMENT: WITH STAINLESS STEEL TRIM (1) 10' DUO-SAFETY FOLDING 585-A LADDER (1) 10' DUO-SAFETY PIKE POLE (CTF) (1) 6' DUO-SAFETY PIKE POLE (CTF) (2) ALUMINUM PIKE POLE TUBES (2) WHELEN M9 L.E.D. OVERHANG SCENE LIGHTS PIERCE CW144639CAI BACK — UP CAMERA (RECESSED) -2.50" OUTLET WITH 2.50" PIPING SWITCH FOR REAR SCENE LIGHTS -SWITCH FOR DECK LIGHTS -90.00 (2) WHELEN M6 L.E.D.— STOP/TAIL LIGHTS TAK-4 72.00 (2) WHELEN M6 L.E.D.-DIRECTIONAL LIGHTS (2) WHELEN M6 L.E.D.-49.00 BACK-UP LIGHTS (2) WHELEN M6 L.E.D.-WARNING LIGHTS 50=== 50 ALL LIGHTS MOUNTED IN WHELEN M6 "PIERCE" BEZEL 20.00 8 8.00° NFPA MIN. -(2) BRITAX 428.102 L.E.D. (2) ZIAMATIC SAC-44-E-—40.00———28.00—<u>—</u> NEPA MIN. MARKER LIGHTS EACH SIDE FOLDING WHEEL CHOCKS 31.50 35.50 BATTERY CHARGER INDICATOR— - 41.62 FC ─ —45.00— SHORELINE RECEPTACLE WITH ---28.00 ——114.50 CA— KUSSMAUL SUPER AUTO EJECT —97**.**00— —174.50 WB— -86.00*—* -367.00 (30'-7.00") APPROX. OAL -JOB NO. MANUFACTURING INC. (1) TRIPLE AIR BOTTLE COMPARTMENT STAINLESS STEEL BODY WITH STAINLESS STEEL DOOR SCALE DATE 1:24 1500-D-500P W/20 GAL. FOAM CELL, DELUGE, GENERATOR DRAWN BY ONE HANNAY ECR1616-17-18 3-WIRE ELECTRIC REWIND CORD REEL WITH 150' OF 10/3 CABLE CHASSIS 08MAR18 IN COMPARTMENT-R1 BST DATA 152" PUMPER RESCUE BODY, HYDRAULIC LADDER RACK . AIR INLET WITH DISCONNECT FITTING LOCATED IN DRIVER SIDE STEP WELL DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS 4. PULL STRAPS FOR DOORS IN COMPARTMENT-D1, D2, D3, P1, P2, P3 MAKE CHECKED BY COHASSET FIRE DEPARTMENT 08MAR18 ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF WITH SIDES IN COMPARTMENT-D1;TWO IN D3,P1,P3 АJА COHASSET, MA PIERCE AS MAY OCCUR OR BE NECESSARY IN ONE ADJUSTABLE TILT/SLIDE-OUT TRAY IN COMPARTMENT-P2 ONE FLOOR MOUNTED SLIDE-OUT TRAY WITH SIDES IN COMPARTMENT-D1,P1,R1 CONSTRUCTION. ₩ 04MAY18 | MMF | JGO MODEL SHEET SIZE SHEET NO. DWG 32245AD 8. ONE SWING-OUT TOOLBOARD WITH PEGBOARD PATTERN IN COMPARTMENT-D2 MINOR DETAILS NOT SHOWN. 9. CIRCUIT BREAKER PANEL LOCATED IN COMPARTMENT-D3 IMPEL FR NO. REV DATE BY CH