



<b>BODY</b> 110' Single Axle Platform Aluminum Body	<b>WATER TANK</b> 500 Gallon Poly Water Tank
<b>COMPT, DRIVER SIDE FRONT</b> Full Height Lap Forward	<b>Foam System</b> Foam System Not Required
<b>COMPT, DRIVER SIDE REAR</b> Full Height Lap Rearward	<b>Foam Cell</b> Foam Cell Not Required
<b>COMPT, PASSENGER SIDE FRONT</b> Full Height Lap Forward	
<b>COMPT, PASSENGER SIDE REAR</b> Full Height Lap Rearward	

<b>CHASSIS</b> Enforcer Chassis 450 HP Cummins L9 Engine	<b>CAB</b> 7000 Enforcer Cab <b>BUMPER</b> 19" Extended Stainless Steel	<b>AXLE, FRONT, CUSTOM</b> 22,800 Lb Dana Axle <b>AXLE, REAR</b> 33,500 Lb Meritor Axle	<b>TRANSMISSION</b> Allison 5th Gen, 3000 EV5 P	<b>PUMPHOUSE</b> 52" Control Zone Side Mount <b>PUMP</b> 1500 GPM Waterous CSU	<b>CROSSLAYS, 1.50"</b> (2) 1.50" Standard Capacity <b>CROSSLAYS, 2.50"</b> (1) 2.50" Standard Capacity	<b>SPEEDLAYS</b> Speedlays Not Required <b>GENERATOR</b> Generator Not Required
--	--	--	--	---	--	--

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONE 1.50" OUTLET WITH 2.00" PIPING AND SWIVEL LOCATED ON TOP THE RIGHT SIDE OF THE FRONT BUMPER
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
- AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
- BATTERY CHARGER LOCATED IN COMPARTMENT PER SHOP ORDER
- BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE OF THE CAB
- EIGHT ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER
- THREE FLOOR MOUNTED SLIDE-OUT TRAYS IN COMPARTMENTS PER SHOP ORDER
- FOUR WHELEN L.E.D. HOSEBED LIGHTS
- NON-RAISED AERIAL PEDESTAL
- 1250 GPM HIGH FLOW WATERWAY

		JOB NO.	32278
TITLE 110' ASCENDANT AERIAL PLATFORM AND BODY ASSEMBLY		SCALE	1:24
MAKE PIERCE		DATE	10JAN18
FOR MARIANNA FIRE RESCUE MARIANNA, FLORIDA		CHECKED BY	CRI
DWG NO. 32278AD		DATE	10JAN18
REV DATE BY CH ENFORCER		SHEET SIZE	SHEET NO. 1 OF 1