



STAINLESS STEEL BODY MAXIMUM O.A.L. 366.75" MAXIMUM O.A.H. 117.00" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- BATTERY CHARGER INDICATOR INSTALLED ON DRIVER'S SEAT RISER
- REVERSED HINGED DOOR ON COMPARTMENTS D3, D4, P2, & P3
- DUAL L.E.D. LIGHT STRIPS FOR WALKING SURFACES INSTALLED IN CARGO AREA
- ALUMINUM PEGBORD WITH TRACKS ON THE REAR WALL OF COMPARTMENT D2 & D3
- CIRCUIT BREAKER PANEL MOUNTED HIGH ON REAR WALL IN COMPARTMENT D3
- ONE 15A / 120V DUPLEX RECEPTACLE INSTALLED IN EMS COMPARTMENT
- ONE 15A / 120V 6-PLACE RECEPTACLE STRIP INSTALLED IN CAB
- ONE 15/20A 120V DUPLEX RECEPTACLE INSTALLED IN COMPARTMENT D3
- EXTERNAL FOAM SYSTEM

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
CHASSIS DATA	TITLE	2000-D-780P, 750G WATER, 30G FOAM, 140" FH/LOW BODY	
MAKE	FOR	(2) CROSSLAYS, DELUGE, GENERATOR, CABLE REEL	
PIERCE		KENNETT FIRE COMPANY NO.1	
MODEL		KENNETT SQUARE, PENNSYLVANIA	
ENFORCER	DWG NO.	32284AD	

Pierce MANUFACTURING INC.

JOB NO. 32284

SCALE 1:24 DATE

DRAWN BY GVH 22MAR18

CHECKED BY NPA 22MAR18

SHEET SIZE D SHEET NO. 1 OF 1