

PUMPER

BODY

Long Aluminum 2nd Gen Pumper

CHASSIS

Enforcer Chassis

CHASSIS

AXLE, FRONT, CUSTOM

22,800 Lb TAK-4 Axle

AXLE, REAR

31,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

26" Extended Painted Steel

CAB

7010 Enforcer Cab

BODY

WATER TANK

1000 Gallon Poly Water Tank

COMPT, PUMPER, REAR

51.25" FF RollUp Rear Compt

COMPT, PUMPER, DRIVER SIDE

171" RollUp Full Height & Depth Front & Rear

COMPT, PUMPER PASS. SIDE

171" RollUp Full Height & Depth Front & Rear

FIRE SUPPRESSION

PUMPHOUSE

45" Control Zone Top Mount

PUMP

2000 GPM Waterous CSU

CROSSLAYS, 1.50"

1.50" Crosslays Not Required

CROSSLAYS, 2.50"

2.50" Crosslay Not Required

SPEEDLAYS

(2) 1.50" W/Troy Std. Capacity
(1) 2.50" W/Troy Std. Capacity

GENERATOR

Harrison 6kW MSV Hydraulic Generator

Foam System

Akron Educator Foam System

Foam Cell

20 Gallon Foam Cell, Not Reduced Water

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB

2. BATTERY CHARGER LOCATED BEHIND DRIVERS SEAT

3. BATTERY CHARGE INDICATOR LOCATED ON DRIVER SIDE OF THE CAB

4. FOUR ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER

5. TWO ADJUSTABLE SLIDE-OUT TRAYS IN COMPARTMENT PER SHOP ORDER

6. TWO TILTING/SLIDE-OUT TRAYS IN COMPARTMENT PER SHOP ORDER

7. ONE SINGLE SWING-OUT TOOL GRID SYSTEM IN COMPARTMENT PER SHOP ORDER

8. ONE DOUBLE SWING-OUT TOOL GRID SYSTEM IN COMPARTMENT PER SHOP ORDER

9. CIRCUIT BREAKER PANEL IN COMPARTMENT PER SHOP ORDER

10. HANNAY BOOSTER REEL MODEL EF24-28-29 LOCATED IN CARGO AREA WITH 200' OF 1.00" BOOSTER HOSE

11. HANNAY CABLE REEL MODEL 1618-17-18 LOCATED IN COMPARTMENT R1 WITH 200' OF 10/3 CABLE

Technical Drawing Details:

- Side View Dimensions:** Overall length 155.50, wheelbase 139.50, height 131.00 (10'-11") APPROX O.A.H.
- Front View Dimensions:** Width 70.00, height 131.00.
- Top View Dimensions:** Overall width 95.00, wheelbase 70.00, overall length 433.75 (36'-1.75") APPROX OAL.
- Component Labels:**
 - (1) PIERCE SIDE VIEW CAMERA EACH SIDE
 - (1) WHELEN 4588 L.E.D. 88" LIGHT BAR WITH (1) WHELEN LIN26 L.E.D. LIGHT EACH SIDE ON SPECIAL LIGHTBAR BRACKET
 - RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
 - (2) BORES STAINLESS STEEL LIGHTED SIGHT RODS
 - (2) WHELEN C6 L.E.D. WARNING LIGHTS IN A COMMON BEZEL EACH SIDE
 - 6.00" FRONT INLET WITH 6.00" SWIVEL AND 6.00" FNST X 5" STORZ ADAPTER
 - (4) WHELEN C6 L.E.D. WARNING LIGHTS EACH SIDE
 - (1) FEDERAL Q2B SIREN
 - (1) FRC SPECTRA L.E.D. VISOR LIGHT
 - (2) HADLEY AIR HORNS
 - (1) WHELEN SA315P SPEAKER WITH 5/STL GRILLE
 - CENTER HOSE TRAY FOR 40' OF 5.00" HOSE
 - (2) WHELEN PFBP12C L.E.D. DECK LIGHTS
 - (2) TROUGHS FOR 6.00" X 10" HARD SUCTION HOSE
 - (1) WHELEN TAL5 L.E.D. TRAFFIC DIRECTING LIGHT RECESSED W/ 5/STL TRIM
 - (2) WHELEN C9 SERIES L.E.D. WARNING LIGHTS
 - DUO-SAFETY LADDER STORAGE
 - (1) 24" 2-SECTION 900A
 - (1) 14" ROOF 775A
 - (1) 10" FOLDING 585A
 - (1) 10" FHU RH-10 PIKE POLE
 - (1) 6" FHU RH-6 PIKE POLE
 - (2) WHELEN 600 L.E.D. WARNING LIGHTS STOP/TAIL LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN PLAST4 BEZELS
 - (3) HOSE BED DIVIDERS
 - (2) 2.50" OUTLETS
 - PIERCE REAR VIEW CAMERA W/ GUARD
 - WILL-BURT NIGHTSCAN NS2-3-600NHL WITH (4) WHELEN PIONEER L.E.D. LIGHT HEADS
 - 8.00" NFPA MIN.
 - 8.00" NFPA MIN.
 - 27.12 R
 - 249.00 WB
 - 433.75 (36'-1.75") APPROX OAL

HOSEBED CAPACITY	
BED 1	200' OF 2.50" D.J. POLY HOSE
BED 2	1000' OF 5.00" D.J. POLY HOSE
BED 3	200' OF 2.50" D.J. POLY HOSE

CUSTOMER APPROVAL				Pierce MANUFACTURING INC.		JOB NO.	32693		
APPROVED BY: _____				TITLE	Pierce Pumper Approval Drawing	SCALE	1:24		
DATE: _____						DATE	DATE		
						DRAWN BY	08MAY18		
				MAKE	FOR	COL	08MAY18		
						CHECKED BY	10MAY18		
				PIERCE		KBO	10MAY18		
						SHEET SIZE	SHEET NO.		
				MODEL	DWG NO.	D	1 OF 1		
				ENFORCER					