



ALUMINUM BODY MAXIMUM O.A.L. 506.00" MAXIMUM O.A.H. 136.50" SIDE ROLL PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- FRONT SUSPENSION WITH 3" JOUCE
- ALUMINUM TREADPLATE ON THE NOTCHED PORTION OF THE CAB ROOF
- BATTERY CHARGE INDICATOR DISPLAYED IN DRIVER'S SIDE CREW CAB WINDOW
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- STABILIZER COMPARTMENTS MODIFIED FOR 18" GROUND PENETRATION
- 5" STILL DRIP PAN/GUARD FOR ROLL-UP DOOR LOCATED AT D1, D3, D4, P1, P3 & P4
- ONE ADJUSTABLE FULL WIDTH/FULL DEPTH SHELF IN COMPARTMENTS D1, D3, D4, D6, P1 & P4
- ONE ADJUSTABLE SLIDE-OUT TRAY IN COMPARTMENT D4 & P4
- 120V RECEPTACLE LOCATED IN COMPARTMENT P2
- ONE FULL WIDTH/DEPTH FLOOR MOUNTED SLIDE-OUT TRAY WITH SIDE SLIDES IN COMPARTMENT D1
- SWING-OUT TOOL BOARD WITH PEGBOARD PATTERN IN COMPARTMENT P3
- 1500 GPM HIGH FLOW WATERWAY
- ALUMINUM PEGBOARD WITH TRACKS ON THE REAR WALL OF COMPARTMENTS D4, P3 & P4
- 4-WAY ALUMINUM ON THE FLOOR OF COMPARTMENTS D2, D3, D5, P2, P3 & P5
- CIRCUIT BREAKER PANEL IN COMPARTMENT D5
- VERTICAL PEGBOARD PARTITION LOCATED IN COMPARTMENT D4
- TRIDENT FOLDING STEPS ON AERIAL DEVICE
- 21.00" AERIAL LIMITED RETRACTION
- L.E.D. LIGHTING ON AERIAL LADDER SECTIONS
- FIRE RESEARCH 3-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP, PUMP PANEL & TURNTABLE

- AERIAL PEDESTAL LOWERED 1.00"
- LIFTING EYE ROPE RESCUE ATTACHMENT AT AERIAL TIP
- BATTERY CHARGER LOCATED BEHIND DRIVER'S SIDE SEAT

REV	DATE	BY	CH	ARROW-XT
07AUG18	SVA	DTS		
17JUL18	SVA	LAB		
09JUL18	SVA	DTS		
31MAY18	SVA	GRM		

		JOB NO.	32703
		SCALE	DATE
TITLE	107' HSL AERIAL LADDER AND BODY ASSEMBLY		
FOR	300 GALLON WATER TANK		
DWG NO.	TOWNSHIP OF UNION FD UNION, NJ		
	32703AD		
	SHEET NO.	1 OF 1	