



ALUMINUM BODY MAXIMUM O.A.H. 142.00" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SEAT RISER
- BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- ONE FLOOR MOUNTED SLIDE-OUT TRAY/STORAGE MODULE IN COMPARTMENT LS4
- 5/8\"/>

- L.E.D. LIGHTING ON AERIAL LADDER SECTIONS
- 120V POWER TO AERIAL TIP
- ATKINSON 3-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP, TURNTABLE AND PUMP PANEL
- ONE WHELEN PSC00CCR L.E.D. STRIP LIGHT MOUNTED AT 45 DEGREES AT REAR OF BOOM SUPPORT
- STABILIZERS MODIFIED FOR 18\"/>

- REMOTE LADDER CONTROLS AT AERIAL TIP
- AERIAL PEDESTAL RAISED 3.00"
- LIFTING EYE RESCUE ATTACHMENT AT AERIAL TIP
- VOGEL LUBE SYSTEM PUMP LOCATED PER SHOP ORDER
- 14.00\"/>

		JOB NO.	32881
		SCALE	DATE
TITLE	107 ASCENDANT AERIAL LADDER & BODY ASSEMBLY	DRAWN BY	SHU
FOR	440 GALLON TANK, 400 GALLONS WATER/40 GALLONS FOAM	CHECKED BY	JBL
	MISSISSAUGA FIRE AND RESCUE SERVICES	SHEET SIZE	SHEET NO.
	MISSISSAUGA, ONTARIO, CANADA	D	1 OF 1
DWG NO.	32881AD		