



ALUMINUM BODY MAXIMUM O.A.H. 123.50" MAXIMUM O.A.L. 429.50" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONE HANNAY ECR1616-17-18 3-WIRE ELECTRIC REWIND CORD REEL WITH 200' OF 12/3 CABLE IN COMPARTMENT-L12,RH1
- ONE HANNAY E1514-17-18 ELECTRIC REWIND AIR REEL WITH 200' OF 0.38" HOSE IN COMPARTMENT-R52
- BATTERY CHARGER LOCATED IN COMPARTMENT-L53
- BATTERY CHARGER INDICATOR LOCATED ON DRIVER SIDE SEAT RISER
- L.E.D. LIGHT STRIPS WALKING SURFACE LIGHTING LOCATED IN THE CARGO AREA
- ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF WITH SIDES IN COMPARTMENT-L52,B1; TWO IN L51, R52; THREE IN L53,R51; FOUR IN R53
- ONE FLOOR MOUNTED SLIDE-OUT TRAY WITH SIDES IN COMPARTMENT-L51,R51,R53
- TWO SLIDE-OUT TOOLBOARDS WITH PEGBOARD PATTERN IN COMPARTMENT-R54
- TWO ADDITIONAL POLY TRAYS SHIPPED LOOSE
- CIRCUIT BREAKER PANEL IN COMPARTMENT-L53
- ONE DUPLEX 120V RECEPTACLE IN COMPARTMENT-L51, L55, R51, R52, R55
- ONE 120V 6-PLACE RECEPTACLE STRIP IN COMPARTMENT-R53
- ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF WITH SIDES IN COMPARTMENT-R52
- ONE VERTICAL DIVIDER IN COMPARTMENT-R52

		JOB NO.	32932
		SCALE	DATE
TITLE 1500-D-750P W/30 GAL. FOAM CELL, DELUGE, GENERATOR 214" PUC RESCUE BODY, LADDERS STORED IN HOSE BED	FOR BOROUGH OF RUNNEMEDE RUNNEMEDE, NJ	DRAWN BY	BST
		CHECKED BY	NPA
DWG NO. 32932AD	ENFORCER	SHEET SIZE	SHEET NO.
			1 OF 1

190EC18	BST	DTS	CHASSIS DATA
130EC18	BST	CSH	MAKE
290CT18	BST	DTS	PIERCE
260CT18	BST	DTS	MODEL
145EP18	LST	AJA	
REV	DATE	BY	CH