



ALUMINUM BODY MAXIMUM O.A.L. 422.50" MAXIMUM O.A.H. 135.00" SIDE ROLL & FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- BATTERY CHARGE INDICATOR LOCATED NEAR DRIVER'S SEAT RISER WITH BRACKET
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF LOCATION IN COMPARTMENT L51, L53, L54, AND R52
- ONE ADJUSTABLE SLIDE-OUT TRAY IN COMPARTMENT L54
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT R51
- AIR INLET/OUTLET W/DISCONNECT FITTING LOCATED ON DS PUMP PANEL

REV	DATE	BY	CH	ARROW XT
20MAR19	LST	CSH		
19NOV18	LST	CSH		
25OCT18	LST	CSH		
07SEP18	LST	CDU		

		JOB NO.	32956
		SCALE	DATE
TITLE	2000-D-3000 GAL POLY, 206" TANKER		DRAWN BY
FOR	(3) XLAYS, DELUGE, GENERATOR, CABLE REEL, ZICO RACK		LST
	GOODWILL FIRE COMPANY		CHECKED BY
	CENTREVILLE, MARYLAND		CDU
DWG NO.	32956AD		SHEET SIZE
			SHEET NO.
			1 OF 1