



- HOSEBED CAPACITIES**
- ① - 300' OF 1.75" HOSE
  - ② - 350' OF 2.50" HOSE
  - ③ - 500' OF 3.00" HOSE
  - ④ - 1000' OF 5.00" HOSE

ALUMINUM BODY    MAXIMUM O.A.L. 360"    MAXIMUM O.A.H. 119.00"    SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
2. BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SEAT RISER
3. DRIP PAN GUARD FOR ROLL-UP DOOR LOCATED IN COMPARTMENTS L51, L52, L53, R51, R52
4. ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF IN COMPARTMENTS L51, L52, L53, R52
5. ONE FULL WIDTH ADJUSTABLE SLIDE-OUT TRAY IN COMPARTMENT R51
6. ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT L51, R51
7. PAC TRAC ON THE REAR WALL OF COMPARTMENT L53
8. ONE BOLT-IN PARTITION LOCATED IN COMPARTMENTS L51/R51 & R51/R51

REV	DATE	BY	CH	ENFORCER
26FEB19	JWO	CSH		MAKE
13FEB19	JWO	KWI		PIERCE
07FEB19	JWO	CSH		MODEL

		JOB NO.	33191
		SCALE	DATE
TITLE	1500-D-500P W/40 G FOAM, 140", FULL HEIGHT DS, LOW PS FDLER, (2) X-LAYS, DELUGE, BOOSTER REEL	DRAWN BY	JWO
FOR	WILMINGTON FIRE DEPARTMENT WILMINGTON, DELEWARE	CHECKED BY	CDU
DWG NO.	33191AD	SHEET SIZE	D
		SHEET NO.	1 OF 1