

PUMPER

BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Enforcer Chassis

CHASSIS

AXLE, FRONT, CUSTOM

18,000 Lb Dana Axle

AXLE, REAR

24,000 Lb Meritor Axle

ENGINE

450 HP Cummins L9

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

16" Extended Stainless Steel

CAB

7010 Enforcer Cab

BODY

WATER TANK

750 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

30.75" FF RollUp Rear Compt

COMPT, PUMPER, DRIVER SIDE

152" RollUp Full Height Front & Rear FDLER

COMPT, PUMPER PASS. SIDE

152" RollUp Full Height Front & Rear FDLER

FIRE SUPPRESSION

PUMPHOUSE

48" Control Zone Side Mount

PUMP

1500 GPM Watertous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Piping For Future Husky 3/12 Foam System

Foam Cell

20 Gallon Foam Cell, Not Reduced Water

Side Roll and Frontal Impact Protection

115.00 (9'-7") APPROX O.A.H.

RUNNING BOARD HOSE TRAY FOR 30" OF 5.00" HOSE

WHELEN FREEDOM IV 81" L.E.D. LIGHTBAR

RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION

(1) WHELEN M6 L.E.D. WARNING LIGHT
(1) WHELEN 600 L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE

(3) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE

(1) WHELEN PIONEER L.E.D. VISOR LIGHT

MOUNTING PROVISIONS FOR WILL-BURT NIGHT SCAN POWERLITE

(2) GROVER AIR HORNS

(1) FEDERAL BP200-Q SPEAKER

CENTER HOSE TRAY FOR 100" OF 1.75" HOSE

HOSEBED CAPACITY

BED 1
750' OF 3.00" D.J. POLY HOSE

BED 2
1000' OF 5.00" D.J. POLY HOSE

BED 3
250' OF 3.00" D.J. POLY HOSE

(2) HOSE BED DIVIDERS

(2) WHELEN L31HRN L.E.D. WARNING LIGHTS

(2) WHELEN M6 L.E.D. SCENE LIGHTS

(1) 2.50" OUTLET

PIERCE REAR VIEW CAMERA

(1) CUP SWITCH FOR HOSE BED LIGHTING

(2) WHELEN M6 L.E.D. WARNING LIGHTS
STOP/TAIL LIGHTS
DIRECTIONAL LIGHTS
BACK-UP LIGHTS

DUO-SAFETY LADDER STORAGE
(1) 24" 2-SECTION 900A
(1) 14" ROOF 775A
(1) 10' FOLDING S85A
(2) ALUMINUM PIKE POLE TUBES
(1) BACKBOARD (2" X 18" X 72")
(1) 8" PIKE POLE
(1) 6" PIKE POLE

5'-7"

8.00° NFPA MIN.

8.00° NFPA MIN.

2.00 85.00 70.00 2.00 48.00 1.50 66.00 31.50 35.50 42.00 28.00 16.00 86.00 187.50 WB 368.50 (30'~8.50") APPROX OAL

8.25 7.75 9.75 8.00 17.00 79.25 20.00 61.00 30.00 56.50 26.50 64.75 47.50 3.00 3.25 8.00

19.75 CLEAR 22.25

(1) FRP L.E.D. LIGHT FOR DESIGNATED WALKING AREA

(2) H1V1Z FT-GE5M L.E.D. SCENE LIGHTS EACH SIDE

78.00 136.00 70.00

18.25 37.50 12.25 19.00 91.00 72.00 14.00 68.00 14.00 28.00 40.00 28.00 96.00

42.25 4.00 36.00 30.75 4.00

27.00 27.13 27.13

31.50 2.25 27.13 4.00

LS2 LS2 LS2 LS1

SS'S LIGHT SHIELD SS'S LIGHT SHIELD

NOTE

DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CREW CAB

3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL

4. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT

5. BATTERY CHARGE INDICATOR LOCATED ON THE DRIVERS SEAT RISER WITH BRACKET

6. FOUR ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER

7. TWO ALUMINUM PEGBOARDS LOCATED IN COMPARTMENTS PER SHOP ORDER

8. TWO 120V RECEPTACLES LOCATED PER SHOP ORDER

				CHASSIS DATA	TITLE	Pierce Pumper Approval Drawing	JOB NO.	33287
				MAKE	FOR	Pierce Stock Field Unit	SCALE	1:24 DATE
				PIERCE			DRAWN BY	COL 30NOV18
				MODEL			CHECKED BY	THS 30NOV18
ENFORCER	14JAN18	COL	THS	ENFORCER	DWG NO.	33287AD	SHEET SIZE	SHEET NO. 1 OF 1
REV	DATE	BY	CH				D	

View File Created 14-JAN-2019 14:25:29