

PUMPER
BODY

Long Aluminum 2nd Gen Pumper

CHASSIS
Enforcer Chassis

CHASSIS
AXLE, FRONT, CUSTOM

19,500 Lb TAK-4

AXLE, REAR

24,000 Lb Dana Axle

ENGINE

400 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

22" Extended Steel Painted

CAB

7010 Enforcer Cab

BODY
WATER TANK

500 Gallon Poly Water Tank

COMPT, PUMPER, REAR

37.75" FF RollUp Rear Compt

COMPT, PUMPER, DRIVER SIDE

161" RollUp Full Height Front & Rear FDLER
Special Depth Upper

COMPT, PUMPER PASS. SIDE

161" RollUp Full Height Front & Rear FDLER
Special Depth Upper

FIRE SUPPRESSION
PUMPHOUSE

45" Control Zone Side Mount

PUMP

1750 GPM Waterous CMU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

2.50" CrossLays Not Required

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Foam System Not Required

Foam Cell

Foam Cell Not Required

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

- VOEL LUBE SYSTEM PUMP LOCATED PER SHOP ORDER
- ALUMINUM TREADPLATE EXTERIOR REAR WALL OF CAB
- 5/STL SCUFFPLATE ON EACH CAB DOOR JAMB
- MOUNTING BASE FOR ANTENNA LOCATED PER SHOP ORDER
- VANNER LIFE STAR POWER INVERTER LOCATED BEHIND DRIVER'S SEAT
- PERIMETER SCENE LIGHTS LOCATED PER SHOP ORDER
- DRIP PAN GUARD FOR ROLL-UP DOOR LOCATED IN LS1,LS2,LS3,RS1,RS2,RS3,B1
- PIERCE L.E.D. DUAL COMPARTMENT LIGHT STRIPS LOCATED PER SHOP ORDER
- SHELF TRACKS LOCATED IN COMPARTMENTS LS1,LS2,LS3,RS1,RS2,RS3,B1

- ONE FULL WIDTH/DEPTH PAINTED ADJUSTABLE SHELF IN COMPARTMENTS LS2,RS2,B1
- TWO FULL WIDTH/DEPTH PAINTED ADJUSTABLE SHELVES IN COMPARTMENTS LS1,RS1,RS3
- THREE FULL WIDTH/DEPTH PAINTED ADJUSTABLE SHELVES IN COMPARTMENT LS3
- PARTITION BETWEEN COMPARTMENTS LS1/B1 AND RS1/B1
- ONE VERTICAL PARTITION IN COMPARTMENTS LS1,LS3
- THREE ADJUSTABLE VERTICAL PARTITIONS IN COMPARTMENT LS1
- ONE POLY MOUNTING BOARD LOCATED IN COMPARTMENT RS2, FIVE IN LS3
- ALL FOLDING STEPS TO BE TRIDENT WITH INTEGRATED L.E.D. LIGHT UNLESS SPECIFIED
- (1) 120V 4-PLACE RECEPTACLE LOCATED IN EMS COMPARTMENT
- AIR INLET WITH DISCONNECT COUPLING ON D.S. PUMP PANEL

- AIR OUTLET WITH SHUT OFF VALVE LOCATED ON D.S. PUMP PANEL
- TWO POLY TOOL BOXES LOCATED IN COMPARTMENT RS2

				CHASSIS DATA
				MAKE
				PIERCE
				MODEL
				ENFORCER
REV	DATE	BY	CH	

 MANUFACTURING INC.	JOB NO.	33808 01-06
	SCALE	DATE
	DRAWN BY	21FEB19
	COL	
TITLE	1750-D-500 GALLON POLY, 161" FDLER, SPCL DEPTH (2)XLAYS, DELUGE, BOOSTER REEL, HYD. LADDER RACK	
	JACKSONVILLE FIRE AND RESCUE JACKSONVILLE, FLORIDA	
FOR	CHECKED BY	24FEB19
	KBO	
DWG NO.	SHEET SIZE	SHEET NO.
	D	1 OF 1

Dimensions:
Overall Length: 381.00 (31'-9.00") OAL
Overall Width: 96.00
Wheelbase: 194.00 WB
Curb-to-Axle: 124.00 CA
Front Overlap: 31.50
Rear Overlap: 16.00
Ground Clearance: 8.00" NFPA MIN.

Labels and Components:
- WHLEN PSTANK L.E.D. WATER LEVEL GAUGE EACH SIDE
- (1) WHLEN PIONEER L.E.D. SCENE LIGHT EACH SIDE
- WHLEN FREEDOM IV LIGHTBAR (72.00" LONG)
- (1) WHLEN PIONEER L.E.D. VISOR LIGHT
- TRUCK-LITE L.E.D. IDENTIFICATION/CLEARANCE LIGHTS
- RETRAC REMOTE CONTROL MIRRORS WITH CONVEX SECTION
- (1) 2.50" OUTLET WITH 2.50" PIPING
- MOUNTING PROVISIONS FOR FEDERAL Q2B SIREN
- BLACK PIERCE POLYUREA COATING ON TOP OF BUMPER FLANGE
- (2) WHLEN M6 L.E.D. WARNING LIGHTS
- (2) WHLEN SA31SP SPEAKERS WITH 5/STL GRILLES
- 22.00" PAINTED STEEL BUMPER WITH CENTER TRAY WITH ADJUSTABLE PARTITION FOR 150" OF 1.75" HOSE ANGLED IN FRONT
- (2) GROVER STUTTERTONE AIR HORNS
- PAINTED TOW EYES
- (3) WHLEN M6 L.E.D. WARNING LIGHTS EACH SIDE
- PIERCE LOGO MUDFLAPS FRONT AND REAR
- STAINLESS STEEL FENDER CROWNS FRONT AND REAR
- (2) DOUBLE AIR BOTTLE COMPARTMENTS P.S.
- (1) DOUBLE AIR BOTTLE COMPARTMENT D.S. WITH STAINLESS STEEL DOORS
- (1) TRUCK-LITE 6011SY L.E.D. DIRECTIONAL/MARKER LIGHT EACH SIDE
- (1) HANNAY BOOSTER REEL MODEL EF24-28-29 W/CAPACITY FOR 200' OF 1.00" BOOSTER HOSE AND 2.00" PIPING
- RUNNING BOARD HOSE TRAY (39" L X 9" W X 10.5" D)
- 12.00" FULL WIDTH STEP
- 4-WAY ALUMINUM HOSEBED COVER
- 26.00" DEEP ALUMINUM 4-WAY TAILBOARD
- HOSEBED COVERS TO OPEN 95-100 DEGREES
- HOSEBED CAPACITIES:
 ① 300' OF 2.50" D.J. POLY HOSE
 ② 1000' OF 5.00" D.J. POLY HOSE
 ③ 800' OF 2.50" D.J. POLY HOSE
 ④ 200' OF 1.75" D.J. POLY HOSE
- 3.00" DELUGE OUTLET WITH 5/5 FLANGE MOUNT AND SECOND HANDWHEEL CONTROL
- ALUMINUM TREADPLATE CROSSLAY COVER
- (2) FRP FLOODLIGHTS
- DIESEL EXHAUST FLUID ACCESS/FUEL FILL REAR OF AXLE
- DOUBLE HARD SUCTION HOSE TROUGHS
- L.E.D. IDENTIFICATION/CLEARANCE LIGHTS
- (3) HOSEBED DIVIDERS WITH HAND HOLD CUTOUTS
- (1) WHLEN PIONEER L.E.D. SCENE LIGHT
- (2) 2.50" OUTLETS
- CUP SWITCH FOR HOSEBED LIGHTS
- CUP SWITCH FOR PPFI SCENE LIGHT
- CUP SWITCH FOR PELCC SCENE LIGHTS
- (2) WHLEN PELCC L.E.D. SCENE LIGHTS
- (2) WHLEN M6 L.E.D. STOP/TAIL LIGHTS
- (2) WHLEN M6 L.E.D. DIRECTIONAL LIGHTS
- (2) WHLEN M6 L.E.D. BACK-UP LIGHTS
- (2) WHLEN M6 L.E.D. WARNING LIGHTS
- HYDRAULIC LADDER RACK FOR CTF DUO-SAFETY LADDERS:
 (1) 24" 2-SECTION 900A
 (1) 14" ROOF 775A
- (2) WHLEN L31HRFN L.E.D. WARNING LIGHTS
- COMPARTMENT FOR:
 (2) BACKBOARDS (72" L X 18" W X 2" T)
 (1) CTF DUO-SAFETY 10" FOLDING LADDER 585
 (3) PIKE POLE TUBES
 (3) FHU F/G 12" PIKE POLES WITH SMOOTH ALUMINUM DOOR AND D-RING LATCHES
- 5'-7" height reference figure

View File Created 23-MAY-2019 11:11:36