/---(1) WHELEN PIONEER P*H2 L.E.D. VISOR LIGHT ALUMINUM TREADPLATE ——— CROSSLAY COVER ——(1) WHELEN M9 L.E.D. PIERCE SIDE WARNING LIGHT VIEW CAMERA (1) GOLIGHT L.E.D. SPOTLIGHT — EACH SIDE PIERCE WIFI ANTENNA ---WHELEN FREEDOM IV — 72″L.E.D. LIGHTBAR HEATED VELVAC 2025 — MIRRORS WITH CONVEX SECTION AND REMOTE CONTROL 126.00 (10'-6") APPROX 0.A.H. (1) WHELEN M6 L.E.D. — WARNING LIGHT (1) WHELEN M6 L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE — (1) 1.50" OUTLET WITH 2.00" PIPING AND SWIVEL 22.00" BUMPER EXTENSION --(2) WHELEN SA315P SPEAKERS WITH S/STL GRILLES (1) FEDERAL BP200-EF SPEAKER —— — (3) WHELEN M6 L.E.D. WARNING LIGHTS (1) TRIPLE AIR BOTTLE COMPARTMENT EACH SIDE WITH POLISH STAINLESS STEEL DOOR -- (2) CROSSLAY HOSE BEDS FOR 200' OF 1.75" HOSE WITH 2.00" PIPING (1) WELDON 9186-8580-29 L.E.D. DIRECTIONAL/MARKER LIGHT EACH SIDE ____10 GALLON FOAM CELL (2) GROVER AIR HORNS —— CENTER HOSE TRAY
FOR 150' OF 1.75" HOSE
W/ TREADPLATE COVER 38.00 (1) CROSSLAY HOSE BED FOR 150' OF 2.50" D.J. HOSE WITH 2.50" PIPING, SINGLE STACK HOSEBED CAPACITIES (1) 800' OF 5.00" D.J. POLY HOSE 2) 500' OF 2.50" D.J. POLY HOSE -120.00-(3) 500' OF 2.50" D.J. POLY HOSE 4) 200' OF 1.75" D.J. POLY HOSE 5 OPEN AREA 3.00" DELUGE OUTLET; AKRON 3433 HI-RISER MONITOR; AKRON 2499 STACKED TIPS AND 3488 SHAPER - DUO-SAFETY LADDERS: (1) 24' 2 SECTION 900A (1) 14' ROOF 775A (1) 10' FOLDING 585A (1) 10' ZICO PIKE POLE (1) 6' ZICO PIKE POLE (2) PIKE POLE TUBES (4) 0.25" HOSE BED DIVIDERS 27.75 CLEAR ---11.00 WITH HANDHOLD CUTOUTS -6.50 **→** 30.25 **→** 20 GALLON FOAM CELL (1) FIRE RESEARCH MAX VISION L.E.D. WATER LEVEL (2) WHELEN PIONEER — —(2) FRP L.E.D. LIGHTS FOR L.E.D. SCENE LIGHTS GAUGE EACH SIDE - - - - --(1) WHELEN M9 L.E.D. WARNING LIGHT EACH SIDE (2) WHELEN M9 L.E.D.— — (1) WHELEN TRUCK WARNING LIGHTS LITE 15 (1) WHELEN PIONEER P*H1 — -(1) 2.50" OUTLET L.E.D. SCENE LIGHT (1) WHELEN TAM85 L.E.D.— TRAFFIC DIRECTING LIGHT (RECESSED) PIERCE REAR VIEW — Oniger of CAMERA (RECESSED) BUZZER BUTTON-COMPARTMENT (1) CUPSWITCH FOR— REAR SCENE LIGHT (2) WHELEN M6 L.E.D. WARNING LIGHTS STOP/TAIL LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN M6 PIERCE BEZELS Pierce Pierce) 8.00° NFPA MIN. NFPA MIN. 31.50 35.50 28.00 16.00 2.00--40.00---—191.50 WB— -9.50 -378.00 (31'-6.00") APPROX OAL DIESEL EXHAUST FLUID/FUEL FILL
ACCESS WITH SINGLE AIR BOTTLE STORAGE
AND COMMON POLISHED S/STL DOOR (2) AIR PACK COMPARTMENTS WITH —— POLISHED STAINLESS STEEL DOOR (ALUMINUM BODY) SIDE ROLL AND FRONTAL IMPACT PROTECTION) MANUFACTURING INC. SCALE DATE 1:24 1500-D-780P, 750 GAL WATER W/ 10 & 20 GAL FOAM CELL DRAWN BY 10. ONE SWING-OUT TOOLBOARD LOCATED IN COMPARTMENT RS2 \E∕ |04SEP19| MMF 1. AIR INLET WITH DISCONNECT COUPLING LOCATED ON THE DRIVER SIDE PUMP PANEL CHASSIS 23MAY19 11. PAC TRAC INSTALLED ON FLOOR OF COMPARTMENT RS1 . AIR OUTLET WITH SHUT OFF VALVE LOCATED IN THE DRIVER SIDE PUMP PANEL MMF (3) CROSSLAYS, BOOSTER REEL, HYDRAULIC LADDER RACK DATA 3. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
4. BATTERY CHARGER LOCATED IN COMPARTMENT LS3
5. BATTERY CHARGE INDICATOR LIGHT LOCATED ON DRIVER SIDE OF THE CAB
6. ONE ADJUSTABLE SHELF LOCATED IN COMPARTMENT LS3, RS3, TWO IN LS1 & B1
7. ONE FLOOR MOUNTED SLIDE-OUT TRAY LOCATED IN COMPARTMENT LS3 RS1 D 20AUG19 MMF JJR DIMENSIONS SHOWN ARE APPROXIMATE 12. ONE FIXED/BOLTED IN SHELF LOCATED IN COMPARTMENT RS1 MAKE CITY OF TUCSON CHECKED BY AND ARE SUBJECT TO MINOR DEVIATIONS C∕|09AUG19| MMF | JJR 28MAY19 SMA TUCSON, ARIZONA PIERCE AS MAY OCCUR OR BE NECESSARY IN ₿/|13JUN19| KLE | JJR SHEET SIZE CONSTRUCTION. TWO ZICO AIR BOTTLE HOLDERS LOCATED IN COMPARTMENT LS3 & RS3 A | 03JUN19 | MMF | SMA MODEL SHEET NO. 33922AD DWG HANNAY BOOSTER REEL MODEL SBEF24-28-29 WITH CAPACITY FOR 150' OF 1.00" MINOR DETAILS NOT SHOWN. REV DATE BY CH ENFORCER BOOSTER HOSE LOCATED IN CARGO AREA

View File Created 06-SEP-2019 06:31:42