



HOSEBED CAPACITIES

①	1200' OF 5.00" D.J. HOSE
②	300' OF 3.00" D.J. HOSE
③	200' OF 1.75" D.J. HOSE

ALUMINUM BODY

MAXIMUM O.A.L. 420.00"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
- DRIP PAN GUARD FOR ROLL-UP DOOR LOCATED IN COMPARTMENTS D1, D2, D3, P1, P2, P3, AND R1
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENTS D1, D3, P1, P3, AND R1
- SWING-OUT TOOL GRID SYSTEM IN COMPARTMENT P2
- (3) ADDITIONAL POLY TRAYS SHIPPED LOOSE
- 140 CFM COMPRESSED AIR FOAM SYSTEM
- CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- ONE HANNAY MODEL E1616-17-18 ELECTRIC REWIND CABLE REEL LOCATED P3
- ONE HANNAY MODEL 2016-17-18 HYDRAULIC REEL LOCATED IN COMPARTMENT P3
- BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER

- ONE 30A, 240V RECEPTACLE IN COMPARTMENT P3
- ADJUSTABLE SHELVES IN COMPARTMENTS (2) D1, D2, D3, & (2) P1
- ONE ADJUSTABLE SLIDE OUT TRAY IN THE UPPER PART OF COMPARTMENT P3
- MIC AND SPEAKER BOX LOCATED AT TOP MOUNT

REV	DATE	BY	CH	ENFORCER
09DEC16	CSQ	DTS	MAKE	
02NOV16	CSQ	DTS	PIERCE	
25SEP16	CSQ	CSH	MODEL	

		JOB NO.	30534
		SCALE	DATE
TITLE	1500-D-960P W/40 GAL FOAM CELL, 161" FH FDLR (3)SPEEDLAYS, LADDERS BESIDE TANK, DELUGE, GENERATOR		
FOR	CARNEY'S POINT TOWNSHIP CARNEY'S POINT, NEW JERSEY		
DWG NO.	30534AD		
DRAWN BY	CSQ	26AUG16	
CHECKED BY	MGE	26AUG16	
SHEET SIZE	D	SHEET NO.	1 OF 1