



ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
2. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
3. AIR INLET W/ DISCONNECT FITTING LOCATED ON DS PUMP PANEL
4. ZIAMATIC SAC-44-E WHEEL CHOCKS WITH DTF BRACKETS
5. ONE HANNAY ELECTRIC REWIND CORD REEL MODEL 1618-17-18 WITH 200' OF 10/3 CABLE LOCATED IN PS HATCH COMPARTMENT
6. HUSKY 12 FOM SYSTEM
7. HERCULES 140 CFM CAFS COMPRESSOR
8. ONE 120V DUPLEX RECEPTACLE LOCATED IN CAB

REV	DATE	BY	CH	VELOCITY	CHASSIS DATA	TITLE
05NOV16	COL	MSA			PIERCE	1500-D-1200 GAL POLY W/50 GAL FOAM CELL, 214" RESCUE (3)XLAYS, CAFS, GENERATOR, LADDERS THROUGH DS BODY
05OCT16	COL	MSA			PIERCE	CENTRAL MAT-SU WASILLA, ALASKA

Pierce MANUFACTURING INC.

JOB NO. 30194
SCALE 1:24
DATE
DRAWN BY COL
040CT16
CHECKED BY
SHEET SIZE D
SHEET NO. 1 OF 2

DWG NO. 30194AD-SH1