



HOSEBED CAPACITIES

- ① 300' OF 3.00" D.J. POLY HOSE
- ② 1000' OF 5.00" D.J. POLY HOSE
- ③ 500' OF 3.00" D.J. POLY HOSE

ALUMINUM BODY SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. BATTERY CHARGER LOCATED IN COMPARTMENT D3
2. BATTERY CHARGER INDICATOR BEHIND DRIVER'S SEAT DISPLAYED THROUGH WINDOW
3. ONE ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENT D2 & D2
4. ONE FLOOR MOUNTED SLIDE-OUT TRAY WITH 2.00" SIDES IN COMPARTMENT D1, D3, P1, & P3
5. PERMANENTLY MOUNTED SHELF WITH INVERTED LIP IN PS HATCH COMPARTMENT
6. HANNAY BOOSTER HOSE REEL MODEL EF34-23-24 WITH CAPACITY OF 200' OF 1.00 BOOSTER HOSE IN COMPARTMENT R1
7. MIC AND SPEAKER LOCATED IN COMPARTMENT D3
8. ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF LOCATED IN COMPARTMENT R1

REV	DATE	BY	CH	DESCRIPTION
1	13FEB18	MMF	JGO	CHASSIS DATA
2	27SEP17	MMF	GHO	MAKE
3	29AUG17	MMF	GHO	PIERCE
4	17JUL17	MMF	CSH	MODEL VELOCITY STEPPED 4X4

		JOB NO.	31392
		SCALE	DATE
TITLE 1500-D-750P 730 GAL WATER W/20 GAL FOAM, 189" RESCUE (3) XLAYS, POLY LADDER RACK, HUSKY 3, LIGHT TOWER	FOR COEYMANS HOLLOW FIRE COMPANY COEYMANS HOLLOW, NEW YORK	DRAWN BY	28JUN17
		CHECKED BY	30JUN17
		SHEET SIZE	SHEET NO.
DWG NO. 31392AD		D	1 OF 1