



ALUMINUM BODY MAXIMUM O.A.L. 415.00" MAXIMUM O.A.H. 133.00"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- KUSSMAUL PUMP PLUS 1000 BATTERY CHARGER/AIR COMPRESSOR LOCATED BEHIND DRIVER'S SEAT
- ONE 12V L.E.D. LIGHT STRIP LOCATED ON EACH SIDE IN THE HOSEBED
- AIR INLET WITH DISCONNECT COUPLING IN D.S. STEP WELL
- ONE ADJUSTABLE FULL WIDTH/FULL DEPTH SHELF IN COMPARTMENT P1; TWO IN D3
- ONE ADJUSTABLE TILT/SLIDE-OUT FULL WIDTH/DEPTH TRAY IN COMPARTMENTS D3, P1 & P4
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENTS D1, P1 & R1; TWO IN D3 & P4
- TWO SWING-OUT ALUMINUM TOOL BOARDS IN COMPARTMENT D2
- ONE ALUMINUM TOOL BOARD ON FLOOR TRAY IN COMPARTMENTS D3 & P4
- ONE VERTICAL PARTITION IN COMPARTMENTS D3, P1 & P4
- ONE VERTICAL BOLT-IN PARTITION BETWEEN COMPARTMENTS D1-R1 & P1-R1
- PERMANENTLY MOUNTED SHELF WITH INVERTED LIP IN COMPARTMENT P4
- ONE 20A, 120V DUPLEX RECEPTACLE LOCATED IN COMPARTMENTS D3, P1, P4 & R1
- ONE 20A, 120V DUPLEX RECEPTACLE IN PASSENGER SIDE ENS CABINET
- CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- CONTROL PANEL FOR CASCADE BREATHING AIR SYSTEM IN COMPARTMENT P3
- SPACESAVER MODEL 100A (2) BOTTLE FILL ENCLOSURE IN COMPARTMENT P3
- THREE 6000 PSI UN AIR CASCADE BOTTLES IN EACH HATCH COMPARTMENT WITH REMOVABLE FLOOR ABOVE
- OIL DRY HOPPER IN HATCH COMPARTMENT ABOVE D1
- ONE HANNAY ELECTRIC REWIND CORD REEL MODEL 1618-17-18 LOCATED IN HATCH ABOVE COMPTS. D3 & P4 WITH 200' OF 10/3 CABLE, AKRON JUNCTION BOX, AND TREADPLATE HOLDER
- ONE HANNAY ELECTRIC REWIND LOW PRESSURE AIR REEL E1514-17-18 IN HATCH ABOVE P3 WITH 150' OF .38" I.D. HOSE

REV	DATE	BY	CH	IMPEL FR
23	JAN16	NPA	PJP	
17	DEC15	NPA	PJP	

		JOB NO.	29362
		SCALE	DATE
TITLE	1500-D-750P W/30 GAL FOAM CELL, 214" RESCUE PUC	DRAWN BY	NPA
FOR	(2) XLAYS, LADDERS BELOW HOSEBED, DELUGE, GENERATOR	CHECKED BY	CSH
DWG NO.	29362AD	SHEET SIZE	SHEET NO.
		D	1 OF 1