



- HOSEBED CAPACITIES**
- ① 500' OF 3.00" D.J. POLY HOSE
 - ② 1000' OF 5.00" D.J. POLY HOSE
 - ③ 200' OF 1.75" D.J. POLY HOSE IN AN ALUMINUM TRAY (7' X 12' X 86")
 - ④ 200' OF 1.75" D.J. POLY HOSE IN AN ALUMINUM TRAY (7' X 12' X 86")
 - ⑤ 200' OF 2.50" D.J. POLY HOSE IN AN ALUMINUM TRAY (9.5' X 12' X 86")

ALUMINUM BODY MAXIMUM O.A.L. 376.00" MAXIMUM O.A.H. 126.00" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
 MINOR DETAILS NOT SHOWN.

- 1. ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- 2. ALUMINUM 4-WAY ON CAB ROOF
- 3. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- 4. 5/8" STL SCUFFPLATE AROUND FUEL FILL OPENING
- 5. ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT D1, P1, P3, & R1
- 6. SWING-OUT TOOL BOARD WITH PEGBOARD PATTERN IN COMPARTMENT D2
- 7. FULL WIDTH ADJUSTABLE SHELVES IN COMPARTMENTS D1, D3, P1, P2, P3, & R1
- 8. DAYTON 4W48 120V FANS LOCATED IN COMPARTMENTS D1, D3, P1, & P3
- 9. 5/8" DRIP PAN LOCATED IN COMPARTMENTS D1, D2, D3, P1, P2, P3, & R1
- 10. CTECH DRAWER ASSEMBLY LOCATED IN COMPARTMENT D3
- 11. TURTLE TILE MATTING LOCATED IN COMPARTMENTS D1, D3, P1, P2, P3, & R1

REV	DATE	BY	CH	ARROW	XT
26JAN17	CSQ	MSA			CHASSIS DATA
16JAN17	CSQ	MSA			MAKE
05DEC16	CSQ	MSA			PIERCE
02DEC16	CSQ	MSA			MODEL
14OCT16	CSQ	SMA			

		JOB NO.	30632-01-03
		SCALE	1:24
TITLE 1750-D-600 GAL POLY W/20G FOAM CELL, 152" FDLER (2) XLAYS, DELUGE, BOOSTER REEL, LADDERS BESIDE TANK		DRAWN BY	CSQ
		CHECKED BY	SMA
FOR WOODINVILLE FIRE & RESCUE WOODINVILLE, WASHINGTON		DWG NO.	30632AD
		SHEET NO.	1 OF 1