



 LIMITED LIFETIME  
**WARRANTY**  
BUILD WITH CONFIDENCE

# PLT-SEC series

Surge protection for power applications

# PLT-SEC series

The PLT-SEC product offers ideal surge protection for power applications from 24 V AC/DC to 230 V AC/DC. The 120 V product obtained a UL Type 2 Listing approval, making it easier to integrate in your applications – saving both time and money. These products include hot-swappable plugs with integrated visual status indication for easy diagnostics. Thermal disconnect for disengaging components during overload conditions ensures safe operational characteristics even in the worst power quality situations.



This product family is a staple component for complying with requirements of the Phoenix Contact Limited Lifetime Warranty program.

## Your advantages

- ✓ UL Type 2 Listed for easy integration into existing applications\*
- ✓ Dual-rated for AC and DC applications
- ✓ 10 kA Short Circuit Current Rating\*
- ✓ Local and remote status indication to easily monitor your system's health
- ✓ Keyed plugs and bases to ensure correct replacement of plugs
- ✓ Integrated marking locations
- ✓ Testable with CHECKMASTER



\* PLT-SEC-T3-120-FM-UT only

Order number	2907916	2907917	2907918	2907919
Description	PLT-SEC-T3-24-FM-UT	PLT-SEC-T3-60-FM-UT	PLT-SEC-T3-120-FM-UT	PLT-SEC-T3-230-FM-UT
Nominal Voltage	24 V AC/DC	60 V AC/DC	120 V AC/DC	230 V AC/DC
MCOV	34 V AC/DC	100 V AC/80 V DC	150 V AC/DC	264 V AC/240 DC
UL Open Type 2 Listed	-	-	✓	-
C1D2	✓	✓	✓	✓
Nominal Discharge Current	1 kA	3 kA	5 kA	5 kA
Replacement plug order number	2907920	2907921	2907922	2907923
Replacement plug description	PLT-SEC-T3-24-P-UT/PT	PLT-SEC-T3-60-P-UT/PT	PLT-SEC-T3-120-P-UT/PT	PLT-SEC-T3-230-P-UT/PT