




















# Pepperl+Fuchs Vending Machine Product Locator

# Pepperl+Fuchs Vending Machine Product Locator

<b>Image</b>	 183715	 206677	 229285	 229286	 229287	 229288	 224885	 224886	 224883	 224884
<b>Vending Position</b>	<b>10</b>	<b>11</b>	<b>12</b>	<b>13</b>	<b>14</b>	<b>15</b>	<b>16</b>	<b>17</b>	<b>18</b>	<b>19</b>
<b>P+F Model #</b>	V3S-GM	V31S-GM	V31-WM	V3-WM	V3-GM	V3S-WM	V1S-G-BK	V1S-W-BK	V1-G-BK	V1-W-BK
<b>Dimensions</b>	3-Pin Nano	4-Pin Nano	4-Pin Nano	3-Pin Nano	3-Pin Nano	3-Pin Nano	4-Pin Micro	4-Pin Micro	4-Pin Micro	4-Pin Micro
<b>Description</b>	Nano 3 pin field-attached male, screw terminal	Nano 4 pin field-attached male, screw terminal	Nano 4 pin field-attached female, 90°, screw terminal	Nano 3 pin field-attached female, 90°, screw terminal	Nano 3 pin field-attached female, screw terminal	Nano 3 pin field-attached, male, 90°, screw terminal	Micro 4 pin field-attached, male, screw terminal	Micro 4 pin field-attached, male, 90°, screw terminal	Micro 4 pin field-attached, female, screw terminal	Micro 4 pin field-attached, female, 90°, screw terminal

<b>Image</b>	 085652	 242306	 087762	 240895	 800733	 802839	 267075-0058	 089585	 087764	 911269
<b>Vending Position</b>	<b>20</b>	<b>21</b>	<b>22</b>	<b>23</b>	<b>24</b>	<b>25</b>	<b>26</b>	<b>27</b>	<b>28</b>	<b>29</b>
<b>P+F Model #</b>	NBB1.5-F41-E2-V3	NEB3-F41-E2-V3	NBB2-12GM50-E0-V1	NBB4-12GM30-E0-V1	NBB4-12GM50-E0-V1	NBB2-8GM25-E0-V3	OBT350-R100-2EP-IO-V31	NBB2-8GM40-E2-V3	NBB2-12GM50-E2-V1	NMB5-12GM65-E2-V1
<b>Dimensions</b>	8mm x 8mm x 40mm	8mm x 8mm x 40mm	12mm x 50mm	12mm x 30mm	12mm x 50mm	8mm x 25mm	37.1mm x 21.5mm x 11mm	8mm x 40mm	12mm x 50mm	12mm x 65mm
<b>Sensing Range</b>	1.5mm	3.0mm	2mm	4mm	4mm	2mm	350mm	2mm	2mm	5mm
<b>Description</b>	Surface mount, shielded, PNP NO, nano 3 pin QD	Surface mount, unshielded, PNP NO, nano 3 pin QD	M12, shielded, NPN NO, Long barrel, micro QD	M12, shielded, NPN NO, short barrel, micro QD	M12, shielded, NPN NO, Long barrel, micro QD	M8, shielded, NPN NO, short barrel, nano QD	R100 BGS, 350mm Range, Visible Red LED, 4-in-1 output, IO-Link, 4-pin M8 Connector	M8, shielded, PNP NO, nano QD	M12, shielded, PNP NO, Long barrel, micro QD	Stainless steel Pile Driver, M12, shielded, PNP NO, micro QD

<b>Image</b>	 087739	 800735		 904077	 904816	 908429	 908432	 909310	 909311	 911268
<b>Vending Position</b>	<b>30</b>	<b>31</b>	<b>32</b>	<b>33</b>	<b>34</b>	<b>35</b>	<b>36</b>	<b>37</b>	<b>38</b>	<b>39</b>
<b>P+F Model #</b>	NBB4-12GM30-E2-V1	NBB4-12GM50-E2-V1		NMB1.5-8GM65-E2-FE-V1	NMB1,5-8GM35-E2-FE-150MM-V1	NMB2-12GM65-E2-FE-V1	NMB2-12GM65-E2-C-FE-V1	NMB1.5-8GM35-E2-C-FE-150MM-V3	NMB1.5-8GM35-E2-C-FE-150MM-V1	NMB5-12GM65-E2-C-V1
<b>Dimensions</b>	12mm x 30mm	12mm x 50mm		8mm x 65mm	8mm x 35mm	12mm x 65mm	12mm x 65mm	8mm x 35mm	8mm x 35mm	12mm x 65mm
<b>Sensing Range</b>	4mm	4mm		1.5mm	1.5mm	2mm	2mm	1.5mm	1.5mm	5mm
<b>Description</b>	M12, shielded, PNP NO, short barrel, micro QD	M12, shielded, PNP NO, Long barrel, micro QD		Pile Driver, shielded, M8, PNP NO, micro QD	Pile Driver, shielded, M8, PNP NO, micro QD 150mm pigtail	Pile Driver shielded, M12, PNP NO, micro QD	Pile Driver, shielded, M12, PNP NO, WFI, micro QD	Pile Driver, shielded, M8, PNP NO, WFI, nano QD, 150 mm pigtail	Pile Driver, shielded, M8, PNP NO, WFI, micro QD, 150 mm pigtail	Pile Driver, shielded, M12, PNP NO, WFI, micro QD

# Pepperl+Fuchs Vending Machine Product Locator

# Pepperl+Fuchs Vending Machine Product Locator





Image	 231035	 231528	 234128	 217482
Vending Position	<b>40</b>	<b>42</b>	<b>44</b>	<b>46</b>
P+F Model #	<b>V1-W-OR5M-POC</b>	<b>V3-WM-OR5M-POC</b>	<b>V3-WM-BK5M-PUR-U</b>	<b>V1-W-BK5M-PUR-U</b>
Dimensions	5 meter	-	5 meter	5 meter
Description	Micro cable, 5 meter, right angle connector, weld slag resistance jacket	Nano 3-pin cable, right angle connector, 5 meter, weld slag resistant jacket	Nano 3 pin cable, right angle connector, 5 meter, PUR	4-Pin Micro DC (M12), right angle, 5 meter black PUR cable, UL Approval









Image	 217480	 218028	 231527	 219135
Vending Position	<b>50</b>	<b>52</b>	<b>54</b>	<b>56</b>
P+F Model #	<b>V3-GM-BK5M-PUR-U</b>	<b>V1-G-BK5M-PUR-U</b>	<b>V3-GM-OR5M-POC</b>	<b>V31-WM-BK5M-PUR-U</b>
Dimensions	5 meter	5 meter	5 meter	5 meter
Description	3 pin, Nano Cordset, 5 meter black PUR cable, female, straight connector	4-Pin, M12 Cordset 5 meter Black PUR 22AWG. Cable Female, Straight	Nano 3 pin cable, 5 meter, straight connector, weld slag resistance jacket	Nano 4 pin cable, right angle connector, 5 meter, PUR

Image	 134072	 134078	 085651	 243809	
Vending Position	<b>60</b>	<b>62</b>	<b>64</b>	<b>66</b>	<b>68</b>
P+F Model #	<b>NBB0.8-5GM25-E0</b>	<b>NBB0.8-4M25-E0</b>	<b>NBB1.5-F41-E2</b>	<b>NEB3-F41-E0</b>	
Dimensions	5mm x 25mm	4mm x 25mm	8mm x 8mm x 40mm	8mm x 8mm x 40mm	
Sensing Range	0.8mm	0.8mm	1.5mm	3.0mm	
Description	M5, shielded, NPN NO, 2 meter preleaded	M4, Sn 0.8 mm, shielded, NPN NO, 2 meter preleaded	Surface mount sensor, shielded, PNP NO, 2 meter preleaded	Surface mount sensor, unshielded, PNP NO, 2 meter preleaded	