

SPECIFICATIONS

Model	VRP12K / VRP12R		VRP24K / VRP24R	
Cooling Performance Data (Cooling Standards: 95°F DB/75°F WB outdoor, 80°F DB/67°F WB indoor)				
Cooling Btu (Rated)	12,000		23,400	
Cooling Btu (Min. - Max)	4,000 - 16,000		12,000 - 28,000	
Voltage	230/208	265	230/208	265
Outdoor Operating Range (°F)	55 - 115		55 - 115	
Power (W)	923		2,138	
SEER	20.0		17.5	
EER	13.0		11.0	
Sensible Heat Ratio	0.71		0.70	
Cooling Amps	4.3		10.0	
Heating Performance Data				
Heating Btu (Rated @ 47° F)	11,500		21,000	
Heating Btu (Rated @ 17° F)	7,100		13,000	
Heating Btu (Min. - Max.)	4,000 - 14,000		12,000 - 26,000	
Heat Pump Outdoor Operating Range (°F)*	0 - 70		0 - 70	
COP (Rated @ 47° F)	3.4		3.1	
COP (Rated @ 17° F)	2.2		2.4	
HSPF	10.0		10.0	
Heating Power (W)	991		1,954	
Heating Amps	4.8	4.1	9.1	7.8

*May experience some loss in capacity. Continuous operation is not guaranteed.

Model	VRP12K	VRP12R	VRP24K	VRP24R
Dimensions (W x D x H)	26 1/8" x 25 1/8" x 52"		26 1/8" x 25 1/8" x 62"	
Shipping Dimensions (W x D x H)	28 1/8" x 27 3/8" x 54 1/2"		28 1/8" x 27 3/8" x 64 1/2"	
Net Weight (lbs.)	215	215	255	255
Shipping Weight (lbs.)	276	276	316	316
R410A Charge (oz.)	49.8	49.8	68.3	68.3

