


PTAC PDH15K5SG

Cooling BTU: **14500/14200**
 Heating BTU: **13300/13000**
 EER: **10.4/10.4**

Volts: **230/208**



Unit Dimensions

Height: **16"**
 Width: **42"**
 Depth: **13 3/4"**

Additional Measurement Specs

Front Cover Height: **16"**
 Front Cover Width: **42"**
 Front Cover Depth: **7 3/4"**
 Cut-Out Height: **16 1/4"**
 Cut-Out Width: **42 1/4"**
 Dimensions With Package: **21 1/2"**
 Net Weight: **124 lbs**
 Shipping Weight: **144 lbs**

Detailed Electrical Information



Voltage: **230/208**
 Volt Range: **253-187**
 Cooling Amps: **6.2/6.7**
 Cooling Watts: **1390/1365**
 Reverse Heating Amps: **6.2/6.7**
 Reverse Heating Watts: **1255/1225**
 Compressor LRA: **28.9**
 Compressor RLA: **5.9**

Additional Performance Specs

Air Circulation: **300 CFM**
 COP: **3.1/3.1**
 Moisture Removal: **3.1 pints per hour**
 Indoor CFM High: **400**
 Indoor CFM Low: **390**
 Sensible Heat Ratio: **0.67**
 Vent CFM: **75**
 R-410A Charge: **39 oz**
 Suggested Retail Price: Please contact the Friedrich Contract Sales Department at (800) 541-6645