

PURCHASER	P.O. #	DATE
PROJECT	LOCATION	
ENGINEER	ARCHITECT	
SUBMITTED BY	FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING BTU/H	VOLTAGE	FRIEDRICH MODEL

Control Features

- Built-in Wi-Fi control on the go with the FriedrichGo™ App
- Smart home / voice command device compatibility (Amazon Alexa and Google Home)
- 24-hour timer
- Remote Control

QuietMaster® Technology

- Heavy duty insulation on inner wall for sound absorption
- Stiffened sheet metal casing to block external noise
- Wide air discharge vents optimize airflow and minimize front panel noise
- Counterweights dampen vibration and decrease sound

Comfort & Convenience

- 3 cooling and fan-only speeds, plus auto fan
- Unique sleep setting
- Auto restart saves settings if power is interrupted
- 8-way air flow control
- Washable, antimicrobial air filter

Installation Features

- One-piece frame (fixed chassis) for fast installation
- Includes standard installation hardware
- Expandable side curtains

Earth Friendly

- ENERGY STAR® qualified models
- Money Saver® setting saves money by operating the fan only when cooling



QuietMaster®
technology



Control
with App



Save big
on energy



Voice command
compatible

SPECIFICATIONS

★ENERGY STAR® models

Model	UPC	Cooling Btu	Heating Btu	Volts Rated	Cooling Amps	Cooling Watts	EER	CEER	Estimated Yearly Energy Cost	Moisture Removal- Pints/HR	Refrigerant	CFM	Wt. Net/Ship Lbs.
<i>FIXED CHASSIS, COOL ONLY (WINDOW INSTALLATION ONLY)</i>													
★ CCF05A10A		5200	—	115	4.3	459	12.1	12.1	\$41	1.0	R410A	141	44/51
★ CCF06A10A		6000	—	115	4.3	492	12.1	12.1	\$45	0.9	R410A	141	44/51
★ CCF08A10A		8000	—	115	5.8	661	12.1	12.0	\$60	1.0	R410A	206	51/57
★ CCF10A10A		10000	—	115	7.3	826	12.1	12.0	\$75	1.2	R410A	282	64/73
★ CCF12A10A		12000	—	115	8.6	992	12.1	12.0	\$90	1.5	R410A	270	73/82

INSTALLATION

Model	Height Inches	Width Inches	Depth Inches	Minimum Extension Into Room Inches	Minimum Extension Outside Inches	Window Width Inches		Carton Dimensions Inches		
						Minimum*	Maximum	Height	Width	Depth
CCF05A10A, CCF06A10A,	13 3/8	18 5/8	15 5/8	—	—	26	36	14 1/2	21 1/2	17 3/4
CCF08A10A	13 3/8	18 5/8	17 5/8	—	—	26	36	14 1/2	21 1/2	18 1/2
CCF10A10A, CCF12A10A	15 1/8	19 7/8	21 3/4	—	—	26	36	17 1/2	21 7/8	23 3/4

All Chill Premier CCF models are designed for window installation only.

* Minimum widths achieved using one side curtain assembly as opposed to both in a standard installation.

CIRCUIT RATING/BREAKER

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
ALL CCF MODELS.	125V-15A	5-15P	6	

