

PURCHASER	P.O. #	DATE
PROJECT	LOCATION	
ENGINEER	ARCHITECT	
SUBMITTED BY	FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING BTU/H	VOLTAGE	FRIEDRICH MODEL

## Control Features

- Built-in Wi-Fi control on the go with the FriedrichGo™ App
- Smart home / voice command device compatibility (Amazon Alexa and Google Home)
- 24-hour timer
- Remote Control

## QuietMaster® Technology

- Heavy duty insulation on inner wall for sound absorption
- Stiffened sheet metal casing to block external noise
- Wide air discharge vents optimize airflow and minimize front panel noise
- Counterweights dampen vibration and decrease sound

## Comfort & Convenience

- 3 cooling and fan-only speeds, plus auto fan
- Unique sleep setting
- Auto restart saves settings if power is interrupted
- 8-way air low control
- Washable, air filter

## Installation Features

- Slide-out chassis for easy removal for maintenance and service
- Includes standard installation hardware
- Expandable side curtains

## Earth Friendly

- ENERGY STAR® qualified models
- Money Saver® setting saves money by operating the fan only when cooling



QuietMaster®  
technology



Control  
with App



Save big  
on energy



Voice command  
compatible

# SPECIFICATIONS

★ ENERGY STAR® models



Model	UPC	Cooling Btu	Heating Btu	Volts Rated	Cooling Amps	Cooling Watts	EER	CEER	Estimated Yearly Energy Cost	Moisture Removal-Pints/HR	Refrigerant	CFM	Wt. Net/Ship Lbs.
<b>SLIDE OUT CHASSIS, COOL ONLY</b>													
★ CCW06B10A		6000	—	115	4.3	492	12.2	12.1	\$44	0.9	R410A	200	44/51
★ CCW08B10A		8000	—	115	5.8	661	12.1	12.0	\$60	1.0	R410A	250	44/61
★ CCW10B10A		10000	—	115	7.3	826	12.1	12.0	\$74	1.2	R410A	300	51/68
★ CCW12B10A		12000	—	115	8.6	992	12.1	12.0	\$89	1.5	R410A	330	64/86
★ CCW15B10A		15000	—	115	11.0	1270	11.9	11.8	\$117	2.0	R410A	400	73/93
★ CCW18B30A		18000	—	230	7.1	1525	11.9	11.8	\$138	2.7	R410A	520	106/136
★ CCW24B30A		24000	—	230	10.2	2308	10.4	10.3	\$209	2.7	R410A	590	117/144
<b>SLIDE OUT CHASSIS, HEAT &amp; COOL</b>													
CEW08B11A		8000	4200	115	6.3	670	11.0	10.9	\$61	2.1	R410A	250	44/61
CEW12B33A		12000	10600	230	4.8	1060	11.0	10.9	\$96	3.3	R410A	265	64/86
CEW18B33A		18000	10600	230	7.2	1600	10.8	10.7	\$144	5.5	R410A	430	106/136
CEW24B33A		24000	10600	230	10.6	2340	9.5	9.4	\$211	6.5	R410A	560	117/144

## INSTALLATION

Model	Height Inches			Width Inches			Depth Inches		Window Width Inches		Carton Dimensions Inches		
	Height	Width	Depth	Minimum Extension Into Room	Minimum Extension Outside	Minimum*	Maximum	Height	Width	Depth			
CCW06B10A, CCW08B10A, CEW08B11A, CCW10B10A, CCW12B10A, CEW12B33A,	14 5/8	19 3/4	23 3/4	—	—	26	36	17	22	26			
CCW15B10A, CCW18B30A, CEW18B33A	18	23 7/8	25 3/8	—	—	26	36	19 3/8	25 5/8	29 5/8			
CCW24B30A, CEW24B33A	18 5/8	27	26 5/8	—	—	26	36	19 1/2	29 1/4	31			

\* Minimum widths achieved using one side curtain assembly as opposed to both in a standard installation.

## CIRCUIT RATING/BREAKER

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
CCW06B10A, CCW08B10A, CCW10B10A, CCW12B10A, CEW08B11A	125V - 15A	5-15P	6	
CCW15B10A			5.5	
CCW18B30A, CCW24B30A	250V - 20A	6-20P	4	
CEW12B33A, CEW18B33A, CEW24B33A			6	

