



Fleet Tracker MGS800

An advanced GPS fleet tracking solution with LTE that provides visibility and insight over your assets and workforce in near real-time

Now you can manage your fleet proactively and respond to your customer needs faster and with increased accuracy. The additional speed of data movement with LTE connectivity enables fast and secure transmission that will future-proof your fleet for years to come.

Get more out of your field staff instantly after a quick professional installation of the Fleet Tracker MGS800. This versatile and feature-rich GPS tracking device provides your fleet managers the best insight into your fleet.

Tackle common fleet issues

- › **Monitor driver behavior:** excessive speeding, harsh braking and racing is dangerous, costing you in maintenance fees and increased fuel consumption.
- › **Get insight into your vehicles like never before:** MGS800 integrates with your vehicle's ECM* and delivers 19 important engine data points.
- › **Prolong your vehicle life:** receive instant DTC code alerts or Check Engine notification and schedule vehicle service before critical breakage occurs.
- › **Know where your fleet is at all times, even in remote locations:** track your vehicles in remote locations where cellular network is unavailable with our Satellite Failover option*.



Get more with less

The Fleet Tracker improves your operational efficiencies because you are able to monitor - on your desk/laptop, tablet or smartphone - information from the field with our easy-to-use software. When you see what you've been missing, you can reduce such things as idle time, off-hours driving, payroll and paid overtime. It reduces wasted time due to increased driver and dispatch efficiency and enhances mobile worker management.

ECM Integration

The MGS800 device connects to your vehicle's Engine Control Module through the OBD-II connector and provides your fleet managers accurate vehicle data like true odometer, DTC codes, engine status and fuel consumption. Take full advantage of the DTC rules and reporting to improve your vehicle performance and fleet efficiency.

Advanced Reporting

The Fleet Complete platform provides your business the ability to assess your fleet performance and identify opportunities to improve your fleet efficiency. Our robust reporting feature offers 25 operational exportable reports in Excel, PDF, CSV, and other formats. Schedule them on a regular basis or run them on-demand and get the detailed data from the field when you need it. Fleet Complete's live dashboard and brand new power reports provide you the up-to-date comprehensive business intelligence to help you take your business to the next level.

Advanced Reporting Adjusted To Your Needs

Covertly installed in your vehicles, MGS800 monitors your vehicles in the field and offers the option to capture additional data from the sensors such as Power Take Off usage, door status, etc.

- › Built-in Bluetooth 2.0 and back-up battery (compatible with HoS)
- › Self-install capable with OBD-II/CANBUS, J1939 or J1708 connections
- › Ability to be hardwired to a vehicle's power source for additional data collection such as: driver ID Integration, emergency button, temperature sensor, door sensor, WiFi and Satellite Failover*

* Additional service fee.

For more information visit fleetcomplete.com or contact your local Fleet Complete regional sales manager.

Technical Specifications

Communication

- LTE/HSPA
- 5-band
- 4G LTE
 - North America: B2(1900), B4(AWS), B5(850), B12(700), B13(700), B17(700)
 - Australia: B3(1800), B5(850), B8(900), B28(700)
- 3G HSPA+
 - North America: B2(1900), B5(850)
 - Australia: B1(2100), B5(850), B8(900)
- UDP/TCP/TFTP/SMS
- SIM: Internal, replaceable
- Antenna: Internal multi-band GSM antenna

Inputs & Outputs

- 6 inputs (3 hi, 2 low, 1 analog)
- 2 outputs

Power

- Input voltage: 8 to 30V DC
- Full operating mode: < 100mA
- Active standby: 13mA at 12V DC
- Sleep mode: < 1mA
- Internal Battery: 3.7V 900mAh, rechargeable

Dimensions & Environment

- Dimensions: ~ 5.6 x 2.9 x 0.8 inches / 142 x 75 x 19 mm
- Weight: ~ 4 ounces / 113 grams
- Temp, operating: -4° - +149° F / -20° - +65° C
- Temp, storage: -40° - +185° F / -40° - +85° C
- Vibration, Impact: SAE J1455

Interfaces

- 3D Accelerometer: Movement detection
- 2 LED status indication
- Connectors: 20-pin 3mm Molex, J1939, J1708 or OBD-II

Default Transmission Rates

- Snapshot every 2 minutes
- Data transmission every 6 minutes

Warranty

- Hardware: 3 years