

# Micro-inverter



## Technical Data

Type	Intisol-SMP600
<b>Input(DC)</b>	
Max. PV Module Power [W]	320 * 2
Max. DC Voltage [V]	50
Operating MPPT Voltage Range [V]	24 - 45
MPPT Voltage Range at Nominal Power [V]	26- 45
Start Voltage [V]	18
Max. DC Current[A]	9.5
Max. DC Short Circuit Current[A]	15
<b>Output(AC)</b>	
Max. AC Power [W]	550
Nominal AC Power [W]	500
Nominal Grid Voltage [V]*	230
Nominal Grid Frequency [Hz]*	50 / 60
Nominal AC Current [A]	2.17
Max. AC Current [A]	2.39
Power Factor	> 0.99
Total Harmonic Distortion (THD)	< 3%
Night time Power Consumption [mW]	120
Max. Units Per Branch	8
<b>Efficiency</b>	
Max. Efficiency	96.7%
CEC Efficiency	96.5%
MPPT Efficiency	99.8%
<b>Physical Structure</b>	
Dimensions (WxHxD) [mm]	218*174*34.5
Weight [kg]	2.35
Environmental Protection Rating	IP 67
Cooling Concept	Natural convection
<b>General Data</b>	
Operating Ambient Temperature Range [ °C]	-40 to +65
Operating Internal Temperature Range [ °C]	-40 to +85
Data Communication Interfaces	PLCC
Guarantee	10 years

\* The AC voltage and frequency range may vary depending on specific country grid

# Inti-SOL

## SMP600



Products updating continues. Any data change will not be informed exclusively.

Address: NO.63, Weixin Road, SIP, China

Tel: +86-512-6956-8216

E-mail: sales@omnik-solar.com

Website: <http://www.omnik-solar.com>

# Micro-inverter



## Technical Data

Type	Intisol-SMP300
<b>Input(DC)</b>	
Max. PV Module Power [W]	320
Max. DC Voltage [V]	50
Operating MPPT Voltage Range [V]	24 - 45
MPPT Voltage Range at Nominal Power [V]	26 - 45
Start Voltage [V]	18
Max. DC Current[A]	9.5
Max. DC Short Circuit Current[A]	15
<b>Output(AC)</b>	
Max. AC Power [W]	270
Nominal AC Power [W]	250
Nominal Grid Voltage [V]*	230
Nominal Grid Frequency [Hz]*	50 / 60
Nominal AC Current [A]	1.09
Max. AC Current [A]	1.19
Power Factor	> 0.99
Total Harmonic Distortion (THD)	< 3%
Night time Power Consumption [mW]	120
Max. Units Per Branch	16
<b>Efficiency</b>	
Max. Efficiency	96.7%
CEC Efficiency	96.5%
MPPT Efficiency	99.8%
<b>Physical Structure</b>	
Dimensions (WxHxD) [mm]	168*162*34.5
Weight [kg]	1.89
Environmental Protection Rating	IP 67
Cooling Concept	Natural convection
<b>General Data</b>	
Operating Ambient Temperature Range [ °C]	-40 to +65
Operating Internal Temperature Range [ °C]	-40 to +85
Data Communication Interfaces	PLCC
Guarantee	10 years

\* The AC voltage and frequency range may vary depending on specific country grid

# Inti-SOL

## SMP300



Products updating continues. Any data change will not be informed exclusively.

Address: NO.63, Weixin Road, SIP, China

Tel: +86-512-6956-8216

E-mail: sales@omnik-solar.com

Website: <http://www.omnik-solar.com>