

CUBISCAN 325 RENTAL RETURN INSTRUCTIONS

Box up the glass

- There should be one piece of glass
- Remove the four round load cell cups and x16 screws and place into a bag in the accessories box (image 6)
- Clean glass & box up into glass kit and set aside for later (image 1)

The component box should include:

- Power cord
- Communication cable
- USB to serial cable
- USB to ethernet
- Small calibration cube
- Ethernet cable
- x2 plastic pin that connects unit to cart
- Display with two wing nuts attached (image 2)
- Four round load cell cups with x16 screws (image 6)
- Four ball bearings (image 9)
- x8 gate screws (image 7)

Begin boxing up the unit

- Remove the display and two wing nuts and place into the accessories box (image 2)
- Remove the x8 gate screws that hold the gate to the unit and place them into a bag and put in the accessories box (image 7)
- Carefully lift up the gate and place onto the frame with foam to protect the frame (image 5)
- Zip tie the gate to the frame (image 5)
- Tighten the gate stop with the gate on the right side of the unit (image 9)

Place the unit into the crate into the two foam inserts

- Put the foam corners in the crate
- Carefully place the unit into the crate (image 3)
- If there was a clear plastic cover provided, place that over the unit to protect it during shipping
- Install the two wood supports over the unit with foam between them and the unit (image 3)
- Place the glass box onto the wood supports and attach with two straps (image 1)
- Place the accessories box into the crate
- Attach the lid

