Setup Instructions for Tailgater Satellite Antenna & DISH Receiver

Setup | Installation | Receiver Activation Software Version L551RGND-N

TABLE OF CONTENTS

First-Time Setup	Page 2
Alternate First-Time Setup	Page 5
Subsequent Setup	Page 8

First-Time Setup of Tailgater Satellite Antenna & DISH Receiver

Setup | Installation | Receiver Activation

Software Version L551RGND-N

INSTRUCTIONS

ESTIMATED SETUP TIME

STEP #1

Position the Tailgater satellite antenna and connect the cabling between the Tailgater and receiver.

IMPORTANT: The Tailgater and receiver are to be connected <u>BEFORE</u> the receiver is plugged in to the power outlet & turned on. If there is power to the receiver before it is connected to the Tailgater, it will begin the wrong satellite sequence and you will not be setting up your equipment accurately.

STEP #2

Power up TV / ViP®211k Receiver / Tailgater satellite antenna.

STEP #3

Installation Wizard: Program TV Remote to Receiver – Follow the on-screen instructions by pressing 'RECORD' on your DISH remote and then selecting 'Continue'



STEP #4

Portable Antenna Setup - Select your current location by state and then select 'Scan'

Dortable Antenna Setup	Dortable Antenna Setup
 1. The portable antenna must be placed on a stable surface with a clear view of the southern sky. 2. Ensure no obstructions block the line of sight from the portable antenna to the sky. 3. Select the state where the portable antenna is currently located below and select "Scan". Image: Image: Im	 1. The p the sc 2. Ensursky. 3. Select Select Currently doing test # 1 of 3 Cancel Select Currently doing test # 1 of 3

NOTE: If you do not see the <u>Portable Antenna Setup</u> screen at this step, please reference the Alternate Instructions starting on page 6 to continue your setup and install.

STEP #5

Installation Wizard: Download Software

2 of 5 This step will take 10-25 minutes.	Step 2 of 5 This step will take 10-25 minutes.
Getting software from satellite Status: In Progress	a) Getting software from satellite Status: Complete
Updating the receiver Status:	b) Updating the receiver Status: In Progress
Please do not disturb or unplug the receiver while this	Please do not disturb or unplug the receiver while this
message appears on screen.	message appears on screen.
When complete, the receiver will power off and restart	When complete, the receiver will power off and restart
before continuing to the next step.	beible continuing to the next step.

Portable Antenna Setup – Select your current location by state and then select 'Scan' (Second Scan)

111	11
Ossin Portable Antenna Setup	G Sh Portable Antenna Setup
 The portable antenna must be placed on a stable surface with a clear view of the southern sky. 	1. The participation 1. The pa
 Ensure no obstructions block the line of sight from the portable antenna to the sky. 	2. Ensur sky. Please wait while your switch installation is checked
Select the state where the portable antenna is currently located below and select "Scan".	3. Selec selec Currently doing test # 1 of 3
A - F Southern California G - L Colorado Connecticut Connecticut	Cancel ancel
Summary	Summary
бтер # 7	5 MINUTES





STEP #9

Installation Wizard: Set Video Resolution – Select your desired resolution and then select 'Test' and 'Save'



NOTE: If you do not see the <u>Set Video Resolution</u> screen at this step or any subsequent screens, please reference the Alternate Instructions, Alternate Step #8 on page 7 to continue your setup and install.

STEP #10	3 MINUTES

Installation Wizard: Connect Receiver to Ethernet or Phone - Select 'Continue'



NOTE: Connecting Ethernet or Phone is not required; it will automatically sequence through if you choose not to connect.

STEP #11	10 MINUTES

Installation Wizard: Activate Receiver



ALTERNATE INSTRUCTIONS

ALTERNATE STEP #4

Installation Wizard: Download Software – Select *#*# on your DISH remote.



Portable Antenna Setup - Select your current location by state and then select 'Scan'

Dortable Antenna Setup	dish Portable Antenna Setup
 The portable antenna must be placed on a stable surface with a clear view of the southern sky. 	1. The provide the scheme sche
 Ensure no obstructions block the line of sight from the portable antenna to the sky. Select the state where the partiable antenna is surrently legated below and 	2. Ensur sky. 2. Select Please wait while your switch installation is checked.
select "Scan".	Currently doing test # 1 of 3
Image: A - F Image: Southern California Image: G - L Image: Colorado Image: M - R Image: Colorado	Cancel ancel
UIS-Z UIDelaware Summary	Summary
Alternate Step #6	

Follow the on-screen instructions to "Turn the receiver off via the remote "Power" button ... "



ALTERNATE STEP #7

Installation Wizard: Download Software – Screen will automatically populate and sequence after powering off receiver.



ALTERNATE STEP #8

Your receiver will automatically restart at the conclusion of Alternate Step #7.

From this screen, select "Power" on your DISH remote, wait for 5 counts, and then select 'Power' on your DISH remote again.



ALTERNATE STEP #9

3 MINUTES

Installation Wizard: Connect Receiver to Ethernet or Phone

Step 4	of 5			
	Testing your c	onnection will take	e 1-3 minutes.	
F	lease do not dista messa	urb or unplug the age appears on so	receiver while this reen.	
Whe	en complete, the r	receiver will contin	ue to the next step	ı.

NOTE: Connecting Ethernet or Phone is not required; it will automatically sequence through if you choose not to connect.

Installation Wizard: Activate Receiver



First-Time Activation of DISH ViP®211k Receiver

To activate, call the applicable number listed below.

- New DISH Customers: 1.800.970.9623
- Existing DISH Customers: 1.888.854.9535

Subsequent Setup of Tailgater Satellite Antenna & DISH Receiver

Setup | Installation

Software Version L551RGND-N

INSTRUCTIONS

ESTIMATED SETUP TIME

STEP #1

Position the Tailgater satellite antenna and connect the cabling between the Tailgater and receiver.

IMPORTANT: The Tailgater and receiver are to be connected BEFORE the receiver is plugged in to the power outlet & turned on. If there is power to the receiver before it is connected to the Tailgater, it will begin the wrong satellite sequence and you will not be setting up your equipment accurately.

STEP #2	

Power up TV / ViP[®]211k Receiver / Tailgater satellite antenna.

STEP #3

Portable Antenna Setup – Select your current location by state and then select 'Scan'



STEP #4

535 Popup



STEP #8

10 MINUTE

330 Popup: Downloading Program Guide

