

# CRYOCONTROL™ FTC System.

Process cooling equipment.



CRYOCONTROL PX5



CRYOCONTROL PX20



CRYOCONTROL PX50 and PX100

The CRYOCONTROL™ Fluid Temperature Control (FTC) system from Messer provides a fast and accurate cooling of process fluids. The CRYOCONTROL PX modules are developed for cooling temperatures down to -148 °F (-100 °C). For cooling down to -180 °F (-120 °C) the CRYOCONTROL XLT50 module is available.

## Advantages

The CRYOCONTROL FTC system quickly and efficiently reduces process temperatures to between -20 and -180 °F. Additional benefits include:

- Fast and flexible - insensitive to process flow or load variations which leads to a rapid and controlled accuracy of +/- 1 °F
- Compact design – ability to fit into the process without modifications or production disturbances
- Easy installation and operation - can be installed either indoors or outdoors, and is fully automated
- Friendly to the environment - nitrogen is an inert gas that can be released to the atmosphere or reused in your process

without harming the environment. The process is free of chlorofluorocarbons and generates no wastewater or secondary pollution

- Creates a high degree of process control and stability in order to increase product quality, yield, and selectivity

## Applications

CRYOCONTROL FTC systems are used widely across Europe and throughout the Americas, efficiently solving cooling demands for a wide variety of customers. Common heat transfer fluids cooled by the system for customers within the pharmaceutical and chemical process industries are:

- Acetone
- Methanol
- SYLTHERM® XLT
- DOWTHERM®
- Limonene
- Brine
- Other heat transfer fluids

## CRYOCONTROL Technical data

PM = Process Medium side	PX5	PX20	PX50	PX100	XLT50
N <sub>2</sub> = Nitrogen side	Process data				
Cooling duty <sup>1</sup> [1000 BTU/hr]	17	68	170	340	170
Flow rate <sup>1</sup> [ft <sup>3</sup> /h]	70	180	350	710	350
Pressure drop: <sup>2</sup> PM [psi]	14.5	14.5	14.5	14.5	14.5
Pressure drop: N <sub>2</sub> [psi]	43.5	43.5	43.5	43.5	43.5
Volume: <sup>3</sup> PM [ft <sup>3</sup> ]	0.07	0.21	0.53	1.38	2.47
Min / Max pressure <sup>4</sup>					
PM [psi (g)]	0 / 275	0 / 275	0 / 275	0 / 275	0 / 275
N <sub>2</sub> [psi (g)]	0 / 275	0 / 275	0 / 275	0 / 275	0 / 275
Min / Max temperature <sup>5</sup>					
PM [°F]	-148 / 120	-148 / 120	-148 / 120	-148 / 120	-180 / 120
N <sub>2</sub> [°F]	-320 / 120	-320 / 120	-320 / 120	-320 / 120	-320 / 120
Dimensions					
Width [in]	35	28	59	59	59
Depth [in]	31	39	53	53	53
Height [in]	26	45	59	59	69
Weight [lb]	130	490	1250	1750	1980
Control system, Allen-Bradley CompactLogix					
Operator panel	Panel View 7	Panel View 7	Panel View 7	Panel View 7	Panel View 7
Connections					
PM: inlet flange	0.75"	1"	1"	2"	2"
outlet flange	0.75"	1"	1"	2"	2"
N <sub>2</sub> : inlet flange	0.75"	1"	1"	1"	1"
outlet flange	0.75"	1"	1"	1.5"	1"
Utilities					
Electrical	120/230 V, 10 A, 50/60 Hz				
Compressed air [psi (g)]	72 - 102	72 - 102	72 - 102	72 - 102	72 - 102
Dew point [°F]	< -4	< -4	< -4	< -4	< -4

<sup>1</sup> These values are nominal values. For most applications, the system can handle loads that range anywhere from 5% to a full 100% of these nominal values. In some cases, the upper load limit can even exceed 100%.

<sup>2</sup> Approximate pressure drop at nominal flow (dependant on temperature and process medium used).

<sup>3</sup> Volume of process medium system inside the unit.

<sup>4</sup> Minimum / Maximum allowable pressure for which the equipment is designed.

<sup>5</sup> Minimum / Maximum allowable temperature for which the equipment is designed. Valid for standard units. Option for maximum temperature of +212 °F available.



### Messer Americas

200 Somerset Corporate Blvd  
Suite 7000  
Bridgewater, NJ 08807  
Phone: 1-800-755-9277  
sales@messer-us.com  
www.messer-us.com

CRYOCONTROL™ is a trademark of Messer Industries USA, Inc.  
SYLTHERM® is a registered trademark of Dow Corning Corp.  
DOWTHERM® is a registered trademark of Dow Chemical Co.  
Messer is not affiliated with Dow Corning or Dow Chemical.



Part of the Messer World

Copyright 2019 Messer North America, Inc. All rights reserved.