


# SAPPHIRE series

## S-65A70-Kx/CXP-12

**Adimec**  
*Excellence in Imaging*



The SAPPHIRE S-65A70 offers the next leap for ultra-high-resolution in-line inspection tools and real time medical imaging by combining 65 megapixel together with frame speeds up to 70 frames per second. The camera delivers a superior performance with a resolution of 9344 x 7000 pixels, high sensitivity, low noise levels and good dynamic range. With a pixel size of 3.2  $\mu\text{m}^2$  this sensor has the right balance between performance, good angular sensitivity and optical format for cost effective optics.

The camera functionality is compatible with other cameras in the SAPPHIRE series: S-25, S-50 and S-65A35.

Typical applications examples: Semiconductors metrology tools; Flat panel glass inspection; Solar panel inspection; Medical

**CoaxPress**<sup>®</sup>

**Preliminary**



65 Megapixel Resolution



Configurable quad CXP12 speed



True Global Shutter CMOS



Low noise performance



Frame speeds up to 70 fps



GPixel sensor

# High Resolution Metrology Camera

## 65 Megapixel

### Target Specifications

|                       | S-65A70  |
|-----------------------|--|
| Sensor                | Gpixel GMAX3265  |
| Pixel size            | 3.2 $\mu\text{m}$ x 3.2 $\mu\text{m}$ with micro lenses      |
| Resolution            | 9344 (H) x 7000 (V)  |
| Optical format        | 37,4 mm (29.9 x 22.4 mm)                                     |
| Video Output          | CoaXPress - V1.1.1 CXP3, 6 and 12 1, 2, 4 lanes configurable |
| Max frame rate        | 70 fps (10 bit)  |
| Dynamic range*        | > 60 dB* (10 bit)  |
| Full Well*            | 10.9 ke  |
| Electronic shutter    | Progressive scan Global Shutter (PLS <1/25000)               |
| Image acquisition     | Timed, TriggerWidth, SyncControl, TimedTriggerControl        |
| Output resolution     | 8 / 10 / 12 Bit  |
| Monochrome / Color    | Monochrome / Color   |
| Power input           | 24 Vdc PoCXP   |
| Power usage           | < 13 W   |
| Operating temperature | 0°C to +30°C and a max sensor temperature of +60°C           |
| Reliability           | MTBF > 75,000 h @ 50°C                                       |
| Weight                | < 400g excluding lens mount                                  |
| Lens mount (optional) | F, M42, T2, TFL-II mount                                     |
| Compliance            | CE, ROHS   |


\*Sensor specification

### Functionality

|  | Black * | Color * |
|--|---------|---------|
| Defect pixel correction                      | √       | √       |
| Manual white balance                         | -       | √       |
| One push white balance                       | -       | √       |
| Region of interest                           | √       | √       |
| Frame counter                                | √       | √       |
| Look-up table                                | √       | √       |
| Digital fine gain (1x to 32x)                | √       | √       |
| Automatic black level control                | √       | √       |
| Dark and bright uniformity corrections       | √       | √       |
| Low Frequency Flat Field Correction (LF FFC) | √       | -       |
| User set data storage                        | √       | √       |
| Programmable I/O                             | √       | √       |

√: standard -: Not available

### Dimensions



### Adimec support

Adimec SAPPHIRE cameras are designed, optimized and calibrated for demanding inspection and metrology applications.

Additionally the Adimec application experts support our customers in integrating the SAPPHIRE camera and tuning the images to fit their measurement.

Please contact your Adimec representative for further assistance.

**For maximum image quality, performance, and reliability in demanding applications - Choose Adimec**

|                           |                    |                    |                    |                   |
|---------------------------|--------------------|--------------------|--------------------|-------------------|
| North America             | Europe             | Japan & Korea      | Asia - Pacific     | China             |
| Phone: (+1) 781-279-0770  | (+31) 40-2353900   | (+81) 3-5968-8377  | (+65) 6334-1236    | (+86)21 6266 1692 |
| Fax: (+1) 781-279-0771    |                    | (+81) 3-5968-8388  | (+65) 6334-1436    |                   |
| E-mail salesus@adimec.com | saleseu@adimec.com | salesjp@adimec.com | salesap@adimec.com |                   |

LFL S65A70 new L&F ver 0.1 - Detailed information on request - Subject to change without notice - Actual products may differ from photos

**Adimec**  
www.adimec.com