

# Demarcation Enclosure



PPC's HB1094RC74xx demarcation enclosure provides a secure compartment for terminating coaxial cables and mounting any combination of drop components.

The enclosure's removable hinged lid has a section that allows for the display of your company's logo. The enclosure can be safeguarded three different ways: two side snap latches, zip-tie/pad lock or locking F-terminator.

The internal mounting arrangement allows for a standardized method of installing coax drop components. All mounts are the same height and spaced in 1/2" increments per SCTE requirements.

To help cover unsightly cable portals and/or components on the side of a home, the back of the enclosure incorporates an 7"x4" section that can easily be removed via a pull-tab.

The open-ended, self-sealing, cable and conduit ports at the bottom of the box allow components to be assembled outside of the enclosure making for quicker installations.

## Features & Benefits

- Weather-resistant thermoplastic housing
- Removable 7"x4" section for covering unsightly installations
- Open-ended cable ports for easier and faster installations
- Ergonomically designed internal mounting boss layout
- Custom logo (optional)



## Product Specifications

UV Resistance	30 Days per ASTM G26-93
Salt Fog	60 Days per ASTM B117-90
Chemical Resistance	30 Days at 100°F and 95% RH Resists chipping and/or cracking when subjected to household chemicals
Material	Copolymer Impact Polypropylene
Dimensions (HxWxD)	11.1" x 10.5" x 4.6"

## Part Number

PPC Part Number	Description
HB1094RC74xx	11.1" x 10.5" x 4.6" Demarcation Enclosure

• xx – Customer Indicator